

# Technical data sheet

## Product features



### Blast chiller 5x GN 1/1 touch control panel 230 V, Right-hinged door

|              |                                  |                                |
|--------------|----------------------------------|--------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00038865                       |
| ISN 0511 PD  | <b>A group of articles - web</b> | Šokery a multifunkční zařízení |



- Shock cooling cycle kg / min (+3 ° C): 25/95
- Shock freeze cycle kg / min (-18 ° C): 10/257
- Minimum device temperature [°C]: -40
- Maximum device temperature [°C]: 10
- Probe: 4-bodová
- Insulation thickness [mm]: 60
- Control type: Touchscreen
- Display size: 9"
- Thaving cycle: Yes

|                            |                    |                                              |             |
|----------------------------|--------------------|----------------------------------------------|-------------|
| <b>SAP Code</b>            | 00038865           | <b>Number of GN / EN</b>                     | 5           |
| <b>Net Width [mm]</b>      | 790                | <b>GN / EN size in device</b>                | GN 1/1      |
| <b>Net Depth [mm]</b>      | 839                | <b>GN device depth</b>                       | 65          |
| <b>Net Height [mm]</b>     | 847                | <b>Shock cooling cycle kg / min (+3 ° C)</b> | 25/95       |
| <b>Net Weight [kg]</b>     | 99.00              | <b>Shock freeze cycle kg / min (-18 ° C)</b> | 10/257      |
| <b>Power electric [kW]</b> | 0.704              | <b>Control type</b>                          | Touchscreen |
| <b>Loading</b>             | 230 V / 1N - 50 Hz |                                              |             |

# Technical data sheet

Technical drawing



**Blast chiller 5x GN 1/1 touch control panel 230 V, Right-hinged door**

|              |                                  |                                |
|--------------|----------------------------------|--------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00038865                       |
| ISN 0511 PD  | <b>A group of articles - web</b> | Šokery a multifunkční zařízení |

# Technical data sheet

## Technical parameters



### Blast chiller 5x GN 1/1 touch control panel 230 V, Right-hinged door

|              |                                  |                                |
|--------------|----------------------------------|--------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00038865                       |
| ISN 0511 PD  | <b>A group of articles - web</b> | Šokery a multifunkční zařízení |

**1. SAP Code:**

00038865

**2. Net Width [mm]:**

790

**3. Net Depth [mm]:**

839

**4. Net Height [mm]:**

847

**5. Net Weight [kg]:**

99.00

**6. Gross Width [mm]:**

830

**7. Gross depth [mm]:**

860

**8. Gross Height [mm]:**

980

**9. Gross Weight [kg]:**

116.00

**10. Device type:**

Electric unit

**11. Exterior color of the device:**

Stainless steel

**12. Opening of device:**

Hinges on the left

**13. Power electric [kW]:**

0.704

**14. Loading:**

230 V / 1N - 50 Hz

**15. Control type:**

Touchscreen

**16. Display size:**

9"

**17. Refrigerant:**

R290

**18. Number of GN / EN:**

5

**19. GN / EN size in device:**

GN 1/1

**20. GN device depth:**

65

**21. Minimum device temperature [°C]:**

-40

**22. Maximum device temperature [°C]:**

10

**23. Shock freeze cycle kg / min (-18 ° C):**

10/257

**24. Shock cooling cycle kg / min (+3 ° C):**

25/95

**25. Insulation thickness [mm]:**

60

**26. Long-term cooling function:**

Yes

**27. Probe:**

4-bodová

**28. Interior lighting:**

Yes

# Technical data sheet

Technical parameters



## Blast chiller 5x GN 1/1 touch control panel 230 V, Right-hinged door

|              |                                  |                                |
|--------------|----------------------------------|--------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00038865                       |
| ISN 0511 PD  | <b>A group of articles - web</b> | Šokery a multifunkční zařízení |

### 29. HACCP:

Yes

### 32. USB port:

Yes, for HACCP and firmware update

### 30. Filter:

Odjímatelný

### 33. Cross-section of conductors CU [mm<sup>2</sup>]:

0,5

### 31. Thaving cycle:

Yes