1850

400.00

4.100

230 V / 1N - 50 Hz

**Product features** 



STEAMBOX gas convection oven 20x GN 2/1 touch digital boiler			
Model	SAP Code	00008613	
SDBB 2021 G	A group of articles - web	Convection machines	
		<ul> <li>Steam type: Symbiotic - boiler and combination (patent)</li> <li>Number of GN / EN: 20</li> <li>GN / EN size in device: GN 2/1</li> <li>GN device depth: 65</li> <li>Control type: Digital</li> <li>Humidity control: MeteoSystem - measurement of humidity in the of advanced moisture adjustment: S saturation modes</li> <li>Delta T heat preparation: Yes</li> <li>Automatic preheating: Yes</li> <li>Multi level cooking: No</li> <li>Door constitution: Vented safety of easy cleaning</li> </ul>	regulation based on direct chamber (patented) Supersteam - two steam
SAP Code	00008613	Power gas [kW]	56.000
Net Width [mm]	1200	Type of gas	Natural Gas
Net Depth [mm]	910	Steam type	Symbiotic - boiler and injection combina-

Number of GN / EN

**GN device depth** 

**Control type** 

GN / EN size in device

tion (patent)

20

65

GN 2/1

Digital

Net Height [mm]

Net Weight [kg]

Loading

Power electric [kW]

Product benefits



ModelSAP CodeSDBB 2021 GA group of articles - web		SAP Code	00008613	
		Convection machines		
1	<b>A symbiotic steam generation system</b> simultaneous use of direct injection and boiler, maintenance of 100% humidity, or its regulation		8 Premix burner the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents backfill and banging	
2	<b>Digital display</b> simple multi-line backlit disp cooking phases	lay of 99 programs with 9	This design saves 30 % of gas compared to conventional burners	
3		neasuring steam saturation in real mode, the only one on the market		Automatic washing integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler
4	<b>Steam tuner</b> a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed
5	<b>Pass-through door</b> the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen		11	<b>Six-speed fan, reversible with automatic</b> <b>calculation of direction change</b> in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually
6	Adaptation for roasting chickens the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat		12	<b>External temperature probe</b> temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe
7	<b>A kit of two machines on top of each other</b> connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation of the lower combi oven		13	<b>Longitudinal insertion to GN</b> penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts
			14	<b>USB</b> downloading service reports software upgrade recipe playback

Technical parameters



STEAMBOX gas convection oven 2	20x GN 2/1 touch digit	tal boiler	
Model SAP Code		00008613	
SDBB 2021 G	A group of articles - web	Convection machines	
<b>1. SAP Code:</b> 00008613		<b>14. Type of gas:</b> Natural Gas	
<b>2. Net Width [mm]:</b> 1200		<b>15. Material:</b> AISI 304	
<b>3. Net Depth [mm]:</b> 910		<b>16. Exterior color of the device:</b> Stainless steel	
<b>4. Net Height [mm]:</b> 1850		<b>17. Adjustable feet:</b> Yes	
<b>5. Net Weight [kg]:</b> 400.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)	
6. Gross Width [mm]: 1320		<b>19. Stacking availability:</b> No	
<b>7. Gross depth [mm]:</b> 1130		<b>20. Control type:</b> Digital	
<b>8. Gross Height [mm]:</b> 2100		<b>21. Additional information:</b> possibility of reverse door opening - handle on the right side (must be specified when ordering)	
<b>9. Gross Weight [kg]:</b> 410.00		<b>22. Steam type:</b> Symbiotic - boiler and injection combination (patent)	
<b>10. Device type:</b> Combined unit		23. Chimney for moisture extraction: Yes	
<b>11. Power electric [kW]:</b> 4.100		<b>24. Delta T heat preparation:</b> Yes	
<b>12. Loading:</b> 230 V / 1N - 50 Hz		<b>25. Automatic preheating:</b> Yes	
<b>13. Power gas [kW]:</b> 56.000		<b>26. Automatic cooling:</b> Yes	

Technical parameters



STEAMBOX gas convection oven 20x GN 2/1 touch digital boiler				
Model	SAP Code	00008613		
SDBB 2021 G A group of articles - web		Convection machines		
<b>27. Unified finishing of meals Easy:</b> No	Service:	<b>41. Interior lighting:</b> Yes		
28. Night cooking:		<b>42. Low temperature heat treatment:</b>		
No		Yes		
<b>29. Multi level cooking:</b> No		<b>43. Number of fans:</b> 2		
<b>30. Advanced moisture adjustment:</b>		<b>44. Number of fan speeds:</b>		
Supersteam - two steam saturation modes		6		
<b>31. Slow cooking:</b> from 30 °C - the possibility of rising		<b>45. Number of programs:</b> 99		
<b>32. Fan stop:</b>		<b>46. USB port:</b>		
Immediate when the door is opened		Yes, for uploading recipes and updating firmware		
<b>33. Lighting type:</b>		<b>47. Door constitution:</b>		
LED lighting in the doors, on both sides		Vented safety double glass, removable for easy cleaning		
<b>34. Cavity material and shape:</b>		<b>48. Number of preset programs:</b>		
AISI 304, with rounded corners for easy cleaning		40		
<b>35. Reversible fan:</b>		<b>49. Number of recipe steps:</b>		
Yes		9		
<b>36. Sustaince box:</b>		<b>50. Minimum device temperature [°C]:</b>		
Yes		30		
<b>37. Probe:</b>		<b>51. Maximum device temperature [°C]:</b>		
Yes		300		
<b>38. Shower:</b>		<b>52. Device heating type:</b>		
Hand winder		Combination of steam and hot air		
<b>39. Distance between the layers [mm]:</b>		<b>53. HACCP:</b>		
70		Yes		
<b>40. Smoke-dry function:</b> No		<b>54. Number of GN / EN:</b> 20		

Technical parameters



STEAMBOX gas convection oven 20x GN 2/1 touch digital boiler			
Model SAP Code		00008613	
SDBB 2021 G	A group of articles - web	Convection machines	
<b>55. GN / EN size in device:</b> GN 2/1		<b>59. Cross-section of conductors CU [mm<sup>2</sup>]:</b> 1,5	
<b>56. GN device depth:</b> 65		<b>60. Diameter nominal:</b> DN 50	
<b>57. Food regeneration:</b> Yes		61. Water supply connection: 3/4"	
<b>58. Connection to a ball valve:</b>			

1/2