Technical data sheet



STEAMBOX gas convection oven 20x GN 1/1 touch digital Automatic cleaning boiler			
Model	SAP Code	00011591	
SDBB 2011 GAM	A group of articles - web	Convection machines	
		 Steam type: Symbiotic - boiler an combination (patent) Number of GN / EN: 20 GN / EN size in device: GN 1/1 GN device depth: 65 Control type: Digital Humidity control: MeteoSystem - measurement of humidity in the of Advanced moisture adjustment: S saturation modes Delta T heat preparation: Yes Automatic preheating: Yes Multi level cooking: No Door constitution: Vented safety of easy cleaning 	regulation based on direct chamber (patented) Supersteam - two steam
SAP Code	00011591	Power gas [kW]	38.000

SAP Code	00011591	Power gas [kW]	38.000
Net Width [mm]	1200	Type of gas	Natural Gas
Net Depth [mm]	910	Steam type	Symbiotic - boiler and injection combina- tion (patent)
Net Height [mm]	1850	Number of GN / EN	20
Net Weight [kg]	300.00	GN / EN size in device	GN 1/1
Power electric [kW]	3.300	GN device depth	65
Loading	230 V / 1N - 50 Hz	Control type	Digital

Technical data sheet

Product benefits



odel		SAP Code	000115	91
SDBB 2011 GAM A group of articles - web			Convection machines	
1 A symbiotic steam generation system simultaneous use of direct injection and boiler, maintenance of 100% humidity, or its regulation		8 Premix burner the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents backfill and banging		
2	Digital display simple multi-line backlit o cooking phases	display of 99 programs with 9	This design saves 30 % of gas compared to conventional burners	
3		uring steam saturation in real the only one on the market	9	Automatic washing integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler
4	Steam tuner a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed
5	Pass-through door the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen		11	Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually
6		i ng chickens ection oven is designed to collect equipped with a container for	12	External temperature probe temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe
7	A kit of two machines on top of each other connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation of the lower combi oven		13 14	Longitudinal insertion to GN penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts USB downloading service reports software upgrade

Technical parameters



STEAMBOX gas convection oven 2	0x GN 1/1 touch digita	Il Automatic cleaning boiler
Model	SAP Code	00011591
SDBB 2011 GAM	A group of articles - web	Convection machines
1. SAP Code: 00011591		14. Type of gas: Natural Gas
2. Net Width [mm]: 1200		15. Material: AISI 304
3. Net Depth [mm]: 910		16. Exterior color of the device: Stainless steel
4. Net Height [mm]: 1850		17. Adjustable feet: Yes
5. Net Weight [kg]: 300.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
6. Gross Width [mm]: 1150		19. Stacking availability: No
7. Gross depth [mm]: 1050		20. Control type: Digital
8. Gross Height [mm]: 2100		21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
9. Gross Weight [kg]: 310.00		22. Steam type: Symbiotic - boiler and injection combination (patent)
10. Device type: Combined unit		23. Chimney for moisture extraction: Yes
11. Power electric [kW]: 3.300		24. Delta T heat preparation: Yes
12. Loading: 230 V / 1N - 50 Hz		25. Automatic preheating: Yes
13. Power gas [kW]: 38.000		26. Automatic cooling: Yes

Technical data sheet

Technical parameters



STEAMBOX gas convection ove	n 20x GN 1/1 touch digital	Automatic cleaning boiler	
Model	SAP Code	00011591	
SDBB 2011 GAM	A group of articles - web	Convection machines	
27. Unified finishing of meals Ea No	syService:	40. Shower: Hand winder	
8. Night cooking: No		41. Distance between the layers [mm]: 70	
29. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping		42. Smoke-dry function: No	
30. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		43. Interior lighting: Yes	
81. Multi level cooking:		44. Low temperature heat treatment:	
No		Yes	
32. Advanced moisture adjustment: Supersteam - two steam saturation modes		45. Number of fans: 2	
33. Slow cooking:		46. Number of fan speeds:	
from 30 °C - the possibility of rising		6	
34. Fan stop:		47. Number of programs:	
Immediate when the door is opened		99	
35. Lighting type:		48. USB port:	
LED lighting in the doors, on both sides		Yes, for uploading recipes and updating firmware	
6. Cavity material and shape:		49. Door constitution:	
AISI 304, with rounded corners for easy cleaning		Vented safety double glass, removable for easy cleaning	
7. Reversible fan:		50. Number of preset programs:	
Yes		40	
8. Sustaince box:		51. Number of recipe steps:	
Yes		9	
89. Probe:		52. Minimum device temperature [°C]:	
Yes		30	

Technical parameters



STEAMBOX gas convection oven 20x GN 1/1 touch digital Automatic cleaning boiler			
Model	SAP Code	00011591	
SDBB 2011 GAM	A group of articles - web	Convection machines	
53. Maximum device temperature [°C]: 300		59. Food regeneration: Yes	
54. Device heating type: Combination of steam and hot air		60. Connection to a ball valve: 1/2	
55. HACCP: Yes		61. Cross-section of conductors CU [mm ²]: 0,75	
56. Number of GN / EN: 20		62. Diameter nominal: DN 50	
57. GN / EN size in device: GN 1/1		63. Water supply connection: 3/4"	
58. GN device depth:			

65