Technical data sheet

Product features

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N		
Model	**SAP Code**	00014496
A 200 ABT RX M Y	**A group of articles - web**	Tunel dishwashers



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD ProSmart soft touch
- Number of programs: 4
- Number of skin: 2
- Maximal rack feed [racks/h]: 200
- Door clear height [mm]: 450
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 0,8 - 1,4
- Washing cycle time [s/basket]: 18 - 37
- Detergent and rinse pump system: Accurate dosing with a peristaltic pump
- Wash pump type: DuoFlow
- Detergent dispenser: Yes
- Rinse aid dispenser: Yes

SAP Code	00014496	**Boiler power [kW]**	9.500
Net Width [mm]	2001	**Basin volume [l]**	70
Net Depth [mm]	813	**Tank power [kW]**	10.500
Net Height [mm]	1615	**Water consumption of the washing cycle [l/basket]**	0,8 - 1,4
Net Weight [kg]	193.00	**Washing cycle time [s/basket]**	18 - 37
Power electric [kW]	23.700	**Maximal rack feed [racks/h]**	200
Loading	400 V / 3N - 50 Hz	**Door clear height [mm]**	450
Boiler capacity [l]	17.00	**Rack size [mm]**	500 x 500


RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical drawing

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N

Model	SAP Code	00014496
A 200 ABT RX M Y	A group of articles - web	Tunel dishwashers



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Product benefits

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N

Model	SAP Code	00014496
A 200 ABT RX M Y	A group of articles - web	Tunel dishwashers

1 Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2 LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

3 Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

4 Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

5 Energy saving

Energy Saving energy saving system due to lowering the temperature of the boiler

- cost saving

6 Protection of fragile dishes

softStart system of gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

7 Possibility of recovery

saving up to 40% of boiler energy
improves the comfort environment of the workplace environment without steam
saves water

- saving on energy and water costs; environmentally friendly system; safe system; pleasant workplace

8 Fast heating

Performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

9 Air break tank

the open system of the boiler rinse, in cooperation with the rinse pump, ensures a constant pressure and temperature of the rinse

- possibility to use in HACCP systems water temperature suitable for sterilization

10 Sliding system

a sliding system that moves the baskets through individual washing zones, the possibility to connect the drive to automatic tables

- quick distribution of dirty dishes

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N

Model	SAP Code	00014496
A 200 ABT RX M Y	A group of articles - web	Tunel dishwashers

1. **SAP Code:**
   00014496
2. **Net Width [mm]:**
   2001
3. **Net Depth [mm]:**
   813
4. **Net Height [mm]:**
   1615
5. **Net Weight [kg]:**
   193.00
6. **Gross Width [mm]:**
   2100
7. **Gross depth [mm]:**
   920
8. **Gross Height [mm]:**
   1850
9. **Gross Weight [kg]:**
   230.00
10. **Device type:**
    Electric unit
11. **Control type:**
    Digital
12. **Material:**
    AISI 304
13. **Power electric [kW]:**
    23.700
14. **Loading:**
    400 V / 3N - 50 Hz
15. **Additional information:**
16. **Rack size [mm]:**
    500 x 500
17. **Number of programs:**
    4
18. **Opening of device:**
    Retractable up
19. **Door clear height [mm]:**
    450
20. **Inlet pressure [bar]:**
    1-4
21. **Adjustable feet:**
    Yes
22. **Number of skin:**
    2
23. **Modular construction:**
    Yes
24. **Pre-wash module:**
    No
25. **Maximal rack feed [racks/h]:**
    200
26. **Self-cleaning cycle:**
    No
27. **Boiler capacity [l]:**
    17.00
28. **Boiler power [kW]:**
    9.500

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N		
Model	**SAP Code**	00014496
A 200 ABT RX M Y	**A group of articles - web**	Tunel dishwashers

29. Basin volume [l]:
70

30. Tank power [kW]:
10.500

31. Number of washing arms:
5

32. Number of rinsing arms:
6

33. Washing arm type:
Firm

34. Washing arm material:
Stainless steel

35. Atmospheric boiler with rinse pump:
Yes

36. Rinsing arm type:
Firm

37. Rinsing arm material:
Stainless steel

38. Deep drawn tank:
Yes

39. Rack support:
welded

40. Tank surface strainers:
stainless steel

41. Boiler thermostat adjust:
Yes

42. Rack feed capacity:
95-150-200

43. Detergent and rinse pump system:
Accurate dosing with a peristaltic pump

44. Hot water electric valve:
Yes

45. Min supply water temperature [°C]:
45

46. Max supply water temperature [°C]:
60

47. Display type:
LCD ProSmart soft touch

48. USB port:
Yes, for Firmware actualisation

49. Self-diagnostics:
Yes

50. Double rinse:
Yes

51. Wash pump type:
DuoFlow

52. Detergent dispenser:
Yes

53. Rinse aid dispenser:
Yes

54. Water consumption of the washing cycle [l/basket]:
0,8 - 1,4

55. Washing cycle time [s/basket]:
18 - 37

56. Rinse water temperature [°C]:
82

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N		
Model	**SAP Code**	00014496
A 200 ABT RX M Y	**A group of articles - web**	Tunel dishwashers

57. Standard equipment for device:
1x glass basket, 1x plate basket, 1x cutlery basket

58. Program ProSpeed:
No

59. Program ProFessional:
No

60. Program ProFessional 2:
No

61. Program ProFessional 4:
No

62. Program ProFessional 6:
No

63. Program ProFessional 8:
No

64. Program ProFessional 10:
No

65. Program ProTemp:
No

66. Program ProSelf:
No

67. Program ProClean:
No

68. Program ProDrain:
No

69. Program ProEco:
No

70. Program ProNew:
No

71. Program ProLong:
No

72. Program ProGlass:
No

73. Program ProPlates:
No

74. Program ProCold:
No

75. Program ProWater:
No

76. Program ProActive:
No

77. Program ProActive 5:
No

78. Program ProActive 7:
No

79. Program ProSteel:
No

80. Program ProSan:
No

81. Program High Capacity:
Yes

82. Program General purpose:
Yes

83. Program Prolonged contact (DIN 10534):
Yes

84. Program Glasses:
Yes

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Rack conveyor dishwasher 200 racks/hour hot water, right exit 400 V / 3N		
Model	**SAP Code**	00014496
A 200 ABT RX M Y	**A group of articles - web**	Tunel dishwashers

85. Cross-section of conductors CU [mm²]:
10

86. Water supply connection:
3/4”

87. Diameter nominal:
DN 50

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062