Product features



STEAMBOX gas convection oven 6x GN 1/1 touch digital Automatic cleaning boiler			
Model	SAP Code	00011588	
SDBB 0611 GAM	A group of articles - web	Convection machines	
		 Steam type: Symbiotic - boiler an combination (patent) Number of GN / EN: 6 GN / EN size in device: GN 1/1 GN device depth: 65 Control type: Digital Humidity control: MeteoSystem - measurement of humidity in the or measurement of humidity in the or saturation modes Delta T heat preparation: Yes Automatic preheating: Yes Multi level cooking: No Door constitution: Vented safety or easy cleaning 	regulation based on direct chamber (patented) Supersteam - two steam
SAP Code	00011588	Power gas [kW]	12.000

SAP Code	00011588	Power gas [kW]	12.000
Net Width [mm]	860	Type of gas	Natural Gas
Net Depth [mm]	795	Steam type	Symbiotic - boiler and injection combina- tion (patent)
Net Height [mm]	835	Number of GN / EN	6
Net Weight [kg]	142.00	GN / EN size in device	GN 1/1
Power electric [kW]	0.400	GN device depth	65
Loading	230 V / 1N - 50 Hz	Control type	Digital

Product benefits



STEAMBOX gas convection oven 6x GN 1/1 touch digital Automatic cleaning boiler					
Model		SAP Code	000115	88	
SDBB 0611 GAM		A group of articles - web	Convection machines		
1	simultaneous use of direct inje	A symbiotic steam generation system simultaneous use of direct injection and boiler, maintenance of 100% humidity, or its regulation		8 Premix burner the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents backfill and banging	
2	Digital display simple multi-line backlit displa cooking phases	ay of 99 programs with 9	This design saves 30 % of gas compared to conventional burners		
3	Weather system patented device for measuring time and in steam mode, the c		9 Automatic washing integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler		
4	Steam tuner a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed	
5	Pass-through door the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen		11	Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually	
6	Adaptation for roasting chickens the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat		12	External temperature probe temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe	
7	A kit of two machines on top of each other connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation of the lower combi oven		13 14	Longitudinal insertion to GN penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts USB downloading service reports software upgrade recipe playback	

Technical parameters



STEAMBOX gas convection oven 6	ix GN 1/1 touch digital	Automatic cleaning boiler	
Model SAP Code		00011588	
SDBB 0611 GAM	A group of articles - web	Convection machines	
1. SAP Code: 00011588		14. Type of gas: Natural Gas	
2. Net Width [mm]: 860		15. Material: AISI 304	
3. Net Depth [mm]: 795		16. Exterior color of the device: Stainless steel	
4. Net Height [mm]: 835		17. Adjustable feet: Yes	
5. Net Weight [kg]: 142.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)	
6. Gross Width [mm]: 860		19. Stacking availability: Yes	
7. Gross depth [mm]: 920		20. Control type: Digital	
8. Gross Height [mm]: 1020		21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)	
9. Gross Weight [kg]: 152.00		22. Steam type: Symbiotic - boiler and injection combination (patent)	
10. Device type: Combined unit		23. Chimney for moisture extraction: Yes	
11. Power electric [kW]: 0.400		24. Delta T heat preparation: Yes	
12. Loading: 230 V / 1N - 50 Hz		25. Automatic preheating: Yes	
13. Power gas [kW]: 12.000		26. Automatic cooling: Yes	

Technical parameters



S	TEAMBOX gas convection oven 6	x GN 1/1 touch digital /	Automatic cleaning boiler		
M	Iodel	SAP Code	00011588		
S	DBB 0611 GAM	A group of articles - web	Convection machines		
27.	Unified finishing of meals Easys No	Service:	40. Shower: volitelná		
28.	28. Night cooking: No		41. Distance between the layers [mm]: 70		
29.	29. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping		42. Smoke-dry function: No		
30.	30. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		43. Interior lighting: Yes		
31.	81. Multi level cooking: No		44. Low temperature heat treatment: Yes		
32.	32. Advanced moisture adjustment: Supersteam - two steam saturation modes		45. Number of fans:		
33.	33. Slow cooking: from 30 °C - the possibility of rising		46. Number of fan speeds: 6		
34.	4. Fan stop: Immediate when the door is opened		47. Number of programs: 99		
35.	5. Lighting type: LED lighting in the doors, on both sides		48. USB port: Yes, for uploading recipes and updating firmware		
36.	6. Cavity material and shape: AISI 304, with rounded corners for easy cleaning		49. Door constitution: Vented safety double glass, removable for easy cleaning		
37.	7. Reversible fan: Yes		50. Number of preset programs: 40		
38.	Sustaince box: Yes		51. Number of recipe steps: 9		
39.	Probe: Optional		52. Minimum device temperature [°C]: 30		

Technical parameters



STEAMBOX gas convection oven 6x GN 1/1 touch digital Automatic cleaning boiler			
Model SAP Code		00011588	
SDBB 0611 GAM	A group of articles - web	Convection machines	
53. Maximum device temperature [°C]: 300		59. Food regeneration: Yes	
54. Device heating type: Combination of steam and hot air		60. Connection to a ball valve: 1/2	
55. HACCP: Yes		61. Cross-section of conductors CU [mm²]: 0,5	
56. Number of GN / EN: 6		62. Diameter nominal: DN 50	
57. GN / EN size in device: GN 1/1		63. Water supply connection: 3/4"	
58. GN device depth:			

65