# Technical data sheet

Product features

RM GASTRO

| Automatic water softener twin tank 2x 8 l 230 V / 1N | | |
|---|---|---|
| **Model** | **SAP Code** | 00007876 |
| DuoSoft 9 | **A group of articles - web** | Water softeners |



- Control type: Digital
- Resin capacity: 0.00
- Inlet pressure [bar]: 2-6
- Material: Polypropylene

| | | | |
|---|---|---|---|
| **SAP Code** | 00007876 | **Net Weight [kg]** | 25.00 |
| **Net Width [mm]** | 250 | **Power electric [kW]** | 0.010 |
| **Net Depth [mm]** | 825 | **Loading** | 230 V / 1N - 50 Hz |
| **Net Height [mm]** | 1080 | **Resin capacity** | 0.00 |



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

# Technical data sheet

Technical drawing

RM GASTRO

| Automatic water softener twin tank 2x 8 l 230 V / 1N | | |
|---|---|---|
| **Model** | **SAP Code** | 00007876 |
| DuoSoft 9 | **A group of articles - web** | Water softeners |



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

# Technical data sheet

Product benefits

RM GASTRO

| Automatic water softener twin tank 2x 8 l 230 V / 1N | | |
|---|---|---|
| **Model** | **SAP Code** | 00007876 |
| DuoSoft 9 | **A group of articles - web** | Water softeners |

**1** **Regeneration of the softener is done only with salt**

light regeneration with salt

- no complex operators are required, regeneration can be handled by trained operators

**2** **Automatic softener regeneration - 2 chambers**

automating the regeneration process

- less operator intervention required; 2x 25 kg salt hopper

**3** **Bypass**

operation of the device is not restricted during regeneration

- no need to stop operation for regeneration



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

# Technical data sheet

Technical parameters

RM GASTRO

| Automatic water softener twin tank 2x 8 l 230 V / 1N | | |
|---|---|---|
| **Model** | **SAP Code** | 00007876 |
| DuoSoft 9 | **A group of articles - web** | Water softeners |

1. **SAP Code:**
   00007876
2. **Net Width [mm]:**
   250
3. **Net Depth [mm]:**
   825
4. **Net Height [mm]:**
   1080
5. **Net Weight [kg]:**
   25.00
6. **Gross Width [mm]:**
   290
7. **Gross depth [mm]:**
   350
8. **Gross Height [mm]:**
   680
9. **Gross Weight [kg]:**
   25.50
10. **Device type:**
    Electric unit
11. **Control type:**
    Digital
12. **Material:**
    Polypropylene
13. **Power electric [kW]:**
    0.010
14. **Loading:**
    230 V / 1N - 50 Hz
15. **Inlet pressure [bar]:**
    2-6
16. **Resin capacity:**
    0.00
17. **Additional information:**
    Water flow (min-max): 0 - 30 / 75 (l/min)
    The consumption for 1 regeneration cycle is 1kg of salt and 200-250 l of water.
18. **Cross-section of conductors CU [mm²]:**
    0,5



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062