



Combi convection steam oven STEAMBOX electric 10x GN 2/1 automatic cleaning boiler 400 V left door		
Model	SAP Code	00014900
STBB 1021 EL	A group of articles - web	Convection machines




- Steam type: Symbiotic boiler and injection combination (patent)
- Number of GN / EN: 10
- GN / EN size in device: GN 2/1
- GN device depth: 65
- Control type: Touchscreen + buttons
- Display size: 9"
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Steamtuner 5-stage system of setting steam saturation by controlled combination of production by boiler or injection
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00014900	Steam type	Symbiotic - boiler and injection combina-tion (patent)
Net Width [mm]	1120	Number of GN / EN	10
Net Depth [mm]	845	GN / EN size in device	GN 2/1
Net Height [mm]	1115	GN device depth	65
Net Weight [kg]	220.00	Control type	Touchscreen + buttons
Power electric [kW]	28.300	Display size	9"
Loading	400 V / 3N - 50 Hz		



Technical drawing

Combi convection steam oven STEAMBOX electric 10x GN 2/1 automatic cleaning boiler 400 V left door		
Model	SAP Code	00014900
STBB 1021 EL	A group of articles - web	Convection machines





### Technical parameters

Combi convection steam oven	STEAMBOX electric 10x	GN 2/1 automatic cleaning boiler 400 V left door
Model	SAP Code	00014900
STBB 1021 EL	A group of articles - web	Convection machines
<b>1. SAP Code:</b> 00014900		<b>14. Exterior color of the device:</b> Stainless steel
2. Net Width [mm]: 1120		<b>15. Adjustable feet:</b> Yes
3. Net Depth [mm]: 845		<b>16. Humidity control:</b> MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
4. Net Height [mm]: 1115		<b>17. Stacking availability:</b> Yes
5. Net Weight [kg]: 220.00		<b>18. Control type:</b> Touchscreen + buttons
<b>6. Gross Width [mm]:</b> 1320		<b>19. Additional information:</b> Version with left door (hinges on the left, handle on the right)
7. Gross depth [mm]: 1130		20. Steam type: Symbiotic - boiler and injection combination (patent)
8. Gross Height [mm]: 1240		21. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 230.00		22. Delayed start: Yes
10. Device type: Electric unit		<b>23. Display size:</b> 9"
<b>11. Power electric [kW]:</b> 28.300		24. Delta T heat preparation: Yes
<b>12. Loading:</b> 400 V / 3N - 50 Hz		25. Automatic preheating: Yes
13. Material:		26. Automatic cooling:

Yes

AISI 304



#### Technical parameters

Model	CADCAL	00014000
Model	SAP Code	00014900
STBB 1021 EL	A group of articles - web	Convection machines
<b>27. Cold smoke-dry functio</b> Yes	n:	40. Heating element material: Incoloy
<b>28. Unified finishing of meals EasyService:</b> Yes		<b>41. Probe:</b> Yes
29. Night cooking: Yes		<b>42. Shower:</b> Hand winder
30. Washing system:  Closed - efficient use of water and washing chemicals by repeated pumping		<b>43. Distance between the layers [mm]:</b> 70
31. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		<b>44. Smoke-dry function:</b> Yes
<b>32. Multi level cooking:</b> Drawer program - control dish separately	of heat treatment for each	<b>45. Interior lighting:</b> Yes
<b>33. Advanced moisture adjustment:</b> Steamtuner - 5-stage system of setting steam saturation by controlled combination of production by boiler or injection		<b>46. Low temperature heat treatment:</b> Yes
<b>34. Slow cooking:</b> from 30 °C - the possibility of rising		<b>47. Number of fans:</b>
<b>85. Fan stop:</b> Immediate when the door is opened		<b>48. Number of fan speeds:</b>
<b>36. Lighting type:</b> LED lighting in the doors, on both sides		<b>49. Number of programs:</b> 1000
<b>37. Cavity material and shape:</b> AISI 304, with rounded corners for easy cleaning		<b>50. USB port:</b> Yes, for uploading recipes and updating firmware
38. Reversible fan: Yes		<b>51. Door constitution:</b> Vented safety double glass, removable for easy cleanin

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

Yes

39. Sustaince box:

100

52. Number of preset programs:



### Technical parameters

Combi convection steam oven STEAMBOX electric 10x GN 2/1 automatic cleaning boiler 400 V left door		
Model	SAP Code	00014900
STBB 1021 EL	A group of articles - web	Convection machines
<b>53. Number of recipe steps:</b> 9		<b>59. GN / EN size in device:</b> GN 2/1
<b>54. Minimum device temperature [°C]:</b> 30		60. GN device depth: 65
<b>55.</b> Maximum device temperature [°C]: 300		<b>61. Food regeneration:</b> Yes
<b>56. Device heating type:</b> Combination of steam and hot air		<b>62. Cross-section of conductors CU [mm²]:</b> 10
<b>57. HACCP:</b> Yes		<b>63. Diameter nominal:</b> DN 50
58. Number of GN / EN:		64. Water supply connection:

3/4"

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

10