

Technical data sheet

Product features



Hood type dishwasher double skin heat recovery system 50x50 - 400 V

Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD multifunction display
- Number of programs: 13
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Drain pump: Yes
- Water consumption of the washing cycle [l/basket]: 2,2
- Washing cycle time [s/basket]: 60-90-180
- Detergent and rinse pump system: Accurate dosing with a peristaltic pump
- Wash pump type: DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: Double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

SAP Code	00011295	Boiler power [kW]	7.000
Net Width [mm]	721	Basin volume [l]	22
Net Depth [mm]	836	Tank power [kW]	2.500
Net Height [mm]	2265	Water consumption of the washing cycle [l/basket]	2,2
Net Weight [kg]	111.00	Washing cycle time [s/basket]	60-90-180
Power electric [kW]	10.200	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	12.00		

Technical drawing



Model

SAP Code

00011295

TT 112 REC ABT

A group of articles - web

Undercounter, continuous and black ware dishwasher



Technical data sheet

Product benefits



Hood type dishwasher double skin heat recovery system 50x50 - 400 V

Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

1

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning
- increased user comfort

3

LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4

Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5

Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6

Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8

Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

9

Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

10

Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

11

Fast heating

performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

12

Possibility of recovery

saving up to 40% of boiler energy improves the comfort environment of the workplace environment without steam saves water

- saving on energy and water costs; environmentally friendly system; safe system; pleasant workplace

Technical data sheet

Technical parameters



Hood type dishwasher double skin heat recovery system 50x50 - 400 V

Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

1. SAP Code:

00011295

2. Net Width [mm]:

721

3. Net Depth [mm]:

836

4. Net Height [mm]:

2265

5. Net Weight [kg]:

111.00

6. Gross Width [mm]:

870

7. Gross depth [mm]:

760

8. Gross Height [mm]:

2314

9. Gross Weight [kg]:

121.00

10. Device type:

Electric unit

11. Control type:

Digital

12. Material:

Stainless steel

13. Power electric [kW]:

10.200

14. Loading:

400 V / 3N - 50 Hz

15. Additional information:

Also possible: 230 V / 3N or 230 V / 1N (must be specified when ordering)

16. Rack size [mm]:

500 x 500

17. Number of programs:

13

18. Opening of device:

Flip up

19. Door clear height [mm]:

465

20. Inlet pressure [bar]:

2-4

21. Adjustable feet:

Yes

22. Number of skin:

2

23. Self-cleaning cycle:

Yes

24. Boiler capacity [l]:

12.00

25. Boiler power [kW]:

7.000

26. Basin volume [l]:

22

27. Tank power [kW]:

2.500

28. Number of arms for both rinsing and washing:

2

Technical data sheet

Technical parameters



Hood type dishwasher double skin heat recovery system 50x50 - 400 V

Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

29. Arm connection:

Hand loosen/tighten screw

30. Washing arm type:

Rotatable two-pronged

31. Washing arm material:

Stainless steel

32. Atmospheric boiler with rinse pump:

Yes

33. Rinsing arm type:

Rotating two-pronged

34. Rinsing arm material:

Stainless steel

35. Deep drawn tank:

Yes

36. Rack support:

Pressed

37. Tank surface strainers:

stainless steel

38. Drain filter:

Double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

49. Hot water electric valve:

Yes

39. Thermostop:

Yes

40. Boiler thermostat adjust:

Yes

41. Rack feed capacity:

60-40-20

42. Detergent and rinse pump system:

Accurate dosing with a peristaltic pump

43. Energy Saving system:

Energy saving system due to lowering the boiler temperature

44. Rinse system:

Stainless steel rinsing arms including stainless steel nozzles with a geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure

45. Heating system:

System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

46. Quick heating system:

System for rapid heating of water in the tank

47. Lift system:

Required lifting force equals 3 kg thanks to counterweights and gentle guidance, reduces operator fatigue

48. Heat recovery:

1 copper-aluminum battery - saving up to 40% of the energy needed to heat the water in the boiler, at the same time, by absorbing the released steam, it eliminates the need to use a hood

64. Program ProFessional:

Yes

Technical data sheet

Technical parameters



Hood type dishwasher double skin heat recovery system 50x50 - 400 V

Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

50. Closing door system:

Reduces noise, dampens the door stop, which could cause damage to dishes

51. Display type:

LCD multifunction display

52. Location of control panel:

On the top

53. USB port:

Yes, for Firmware actualisation

54. Drain pump:

Yes

55. Self-diagnostics:

Yes

56. Wash pump type:

DuoFlow

57. Detergent dispenser:

Yes

58. Rinse aid dispenser:

Yes

59. Water consumption of the washing cycle [l/basket]:

2,2

60. Washing cycle time [s/basket]:

60-90-180

61. Rinse water temperature [°C]:

80

62. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

63. Program ProSpeed:

Yes

65. Program ProTemp:

Yes

66. Program ProClean:

Yes

67. Program ProDrain:

Yes

68. Program ProEco:

Yes

69. Program ProNew:

Yes

70. Program ProLong:

Yes

71. Program ProGlass:

Yes

72. Program ProWater:

Yes

73. Program ProActive:

Yes

74. Program ProSteel:

Yes

75. Program ProSan:

Yes

76. Cross-section of conductors CU [mm²]:

2,5

77. Water supply connection:

3/4"

78. Diameter nominal:

DN 50