

# Technical data sheet

Product features



## Boiling kettle electric indirect 100l

|              |                                  |                 |
|--------------|----------------------------------|-----------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00013683        |
| PI100A-98ET  | <b>A group of articles - web</b> | Boiling kettles |

– Device type: Electric unit

|                        |          |                            |                    |
|------------------------|----------|----------------------------|--------------------|
| <b>SAP Code</b>        | 00013683 | <b>Net Weight [kg]</b>     | 97.00              |
| <b>Net Width [mm]</b>  | 800      | <b>Power electric [kW]</b> | 16.000             |
| <b>Net Depth [mm]</b>  | 900      | <b>Loading</b>             | 400 V / 3N - 50 Hz |
| <b>Net Height [mm]</b> | 900      |                            |                    |

# Technical data sheet

Technical drawing



## Boiling kettle electric indirect 100l

|                          |                           |                 |
|--------------------------|---------------------------|-----------------|
| Model<br><br>PI100A-98ET | SAP Code                  | 00013683        |
|                          | A group of articles - web | Boiling kettles |

# Technical data sheet

Technical parameters



## Boiling kettle electric indirect 100l

|              |                                  |                 |
|--------------|----------------------------------|-----------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00013683        |
| PI100A-98ET  | <b>A group of articles - web</b> | Boiling kettles |

**1. SAP Code:**

00013683

**2. Net Width [mm]:**

800

**3. Net Depth [mm]:**

900

**4. Net Height [mm]:**

900

**5. Net Weight [kg]:**

97.00

**6. Gross Width [mm]:**

870

**7. Gross depth [mm]:**

1070

**8. Gross Height [mm]:**

1150

**9. Gross Weight [kg]:**

107.00

**10. Device type:**

Electric unit

**11. Power electric [kW]:**

16.000

**12. Loading:**

400 V / 3N - 50 Hz

**13. Cross-section of conductors CU [mm<sup>2</sup>]:**

5

**14. Water supply connection:**

1/2"