

# Technical data sheet

## Product features



### Pot and pan washer double skin with drain pump 50x60 - 400 V

|              |                                  |  |
|--------------|----------------------------------|--|
| <b>Model</b> | <b>SAP Code</b>                  | 00011965   |
| S 97 P ABT   | <b>A group of articles - web</b> | Undercounter, continuous and black ware dishwasher |



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD multifunction display
- Number of programs: 14
- Number of skin: 2
- Door clear height [mm]: 405
- Rack size [mm]: 500 x 600
- Drain pump: Yes
- Water consumption of the washing cycle [l/basket]: 2,4
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: Evolution3 - double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

|                            |                    |  |           |
|----------------------------|--------------------|--|-----------|
| <b>SAP Code</b>            | 00011965           | <b>Boiler capacity [ l ]</b>                             | 6.00      |
| <b>Net Width [mm]</b>      | 575                | <b>Boiler power [kW]</b>                                 | 6.000     |
| <b>Net Depth [mm]</b>      | 700                | <b>Basin volume [l]</b>                                  | 23        |
| <b>Net Height [mm]</b>     | 1290               | <b>Tank power [kW]</b>                                   | 2.100     |
| <b>Net Weight [kg]</b>     | 73.00              | <b>Water consumption of the washing cycle [l/basket]</b> | 2,4       |
| <b>Power electric [kW]</b> | 8.800              | <b>Door clear height [mm]</b>                            | 405       |
| <b>Loading</b>             | 400 V / 3N - 50 Hz | <b>Rack size [mm]</b>                                    | 500 x 600 |



# Technical data sheet

Technical drawing



## Pot and pan washer double skin with drain pump 50x60 - 400 V

|              |                                  |  |
|--------------|----------------------------------|--|
| <b>Model</b> | <b>SAP Code</b>                  | 00011965   |
| S 97 P ABT   | <b>A group of articles - web</b> | Undercounter, continuous and black ware dishwasher |



# Technical data sheet

## Product benefits



### Pot and pan washer double skin with drain pump 50x60 - 400 V

|              |                                  |  |
|--------------|----------------------------------|--|
| <b>Model</b> | <b>SAP Code</b>                  | 00011965   |
| S 97 P ABT   | <b>A group of articles - web</b> | Undercounter, continuous and black ware dishwasher |

**1** **Stainless steel outer shell construction**  
round construction with stainless steel, rounded edges, Deep-drawn bathtub  
– easy cleaning, high hygiene standard, long service life

**2** **Stainless steel washing arms**  
upper and lower arms with stainless steel, separated for washing and rinsing, triple upper arm  
– easy and safe handling during cleaning; higher user comfort

**3** **LED Display**  
smartScreen, a large color graphic display showing the washing progress  
– easy control of the dishwasher operation  
– continuous information on the status of the wash cycle  
– diagnostics in the event of a fault

**4** **Double pump**  
unique two-way DuoFlow pump  
– distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

**5** **Detergent dispensers**  
two detergent and rinse aid dispensers  
– precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

**6** **Double filter system**  
the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency  
– higher washing efficiency; longer life of the washing bath

**7** **Energy saving**  
energy saving energy saving system due to lowering the temperature of the boiler  
– cost saving

**8** **Protection of fragile dishes**  
softstart system for gradual start of washing programs to protect fragile dishes  
– protects stemmed glasses and other fragile utensils

**9** **Double shell construction**  
stainless steel construction with insulated double jacket  
– quiet operation  
– energy saving

**10** **Fast heating**  
performance management allows the current running of the boiler and basins body  
– quick first warm-up of the dishwasher  
– smooth operation

**11** **Air break tank**  
the open system of the boiler rinse, in cooperation with the rinse pump, ensures a constant pressure and temperature of the rinse  
– possibility to use in HACCP systems water temperature suitable for sterilization

# Technical data sheet

Technical parameters



## Pot and pan washer double skin with drain pump 50x60 - 400 V

|                   |                                  |  |
|-------------------|----------------------------------|--|
| <b>Model</b>      | <b>SAP Code</b>                  | 00011965   |
| <b>S 97 P ABT</b> | <b>A group of articles - web</b> | Undercounter, continuous and black ware dishwasher |

**1. SAP Code:**

00011965

**2. Net Width [mm]:**

575

**3. Net Depth [mm]:**

700

**4. Net Height [mm]:**

1290

**5. Net Weight [kg]:**

73.00

**6. Gross Width [mm]:**

780

**7. Gross depth [mm]:**

670

**8. Gross Height [mm]:**

1250

**9. Gross Weight [kg]:**

79.00

**10. Device type:**

Electric unit

**11. Control type:**

Digital

**12. Material:**

AISI 304

**13. Power electric [kW]:**

8.800

**14. Loading:**

400 V / 3N - 50 Hz

**15. Number of programs:**

14

**16. Opening of device:**

Tilting down

**17. Door clear height [mm]:**

405

**18. Inlet pressure [bar]:**

2-4

**19. Adjustable feet:**

Yes

**20. Number of skin:**

2

**21. Self-cleaning cycle:**

Yes

**22. Boiler capacity [ l ]:**

6.00

**23. Boiler power [kW]:**

6.000

**24. Basin volume [l]:**

23

**25. Tank power [kW]:**

2.100

**26. Number of arms for both rinsing and washing:**

2

**27. Arm connection:**

Click-clack - easy removal with one hand

**28. Washing arm type:**

Rotating trident

# Technical data sheet

## Technical parameters



### Pot and pan washer double skin with drain pump 50x60 - 400 V

|              |                                  |  |
|--------------|----------------------------------|--|
| <b>Model</b> | <b>SAP Code</b>                  | 00011965   |
| S 97 P ABT   | <b>A group of articles - web</b> | Undercounter, continuous and black ware dishwasher |

**29. Washing arm material:**

Composite

**30. Atmospheric boiler with rinse pump:**

Yes

**31. Rinsing arm type:**

Rotating trident

**32. Rinsing arm material:**

Composite

**33. Deep drawn tank:**

Yes

**34. Rack support:**

Pressed

**35. Tank surface strainers:**

stainless steel

**36. Drain filter:**

Evolution3 - double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

**37. Thermostop:**

Yes

**38. Boiler thermostat adjust:**

Yes

**39. Detergent and rinse pump system:**

ProDose - accurate dosing with a peristaltic pump

**40. Energy Saving system:**

EnergySaving - Energy saving system due to lowering the boiler temperature

**41. Rinse system:**

ProRinse - composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure

**42. Heating system:**

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

**43. Quick heating system:**

QuickReady - System for rapid heating of water in the tank

**44. Hot water electric valve:**

Yes

**45. Closing door system:**

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

**46. Rack size [mm]:**

500 x 600

**47. Display type:**

LCD multifunction display

**48. USB port:**

Yes, for Firmware actualisation

**49. Drain pump:**

Yes

**50. Self-diagnostics:**

Yes

# Technical data sheet

Technical parameters



## Pot and pan washer double skin with drain pump 50x60 - 400 V

|              |                                  |  |
|--------------|----------------------------------|--|
| <b>Model</b> | <b>SAP Code</b>                  | 00011965   |
| S 97 P ABT   | <b>A group of articles - web</b> | Undercounter, continuous and black ware dishwasher |

**51. Wash pump type:**

two-way - DuoFlow

**52. Detergent dispenser:**

Yes

**53. Rinse aid dispenser:**

Yes

**54. Water consumption of the washing cycle [l/basket]:**

2,4

**55. Additional information:**

Also possible: 230 V / 3N or 230 V / 1N (must be specified when ordering)

**56. Program ProFessional 2:**

Yes

**57. Program ProFessional 4:**

Yes

**58. Program ProFessional 6:**

Yes

**59. Program ProFessional 8:**

Yes

**60. Program ProFessional 10:**

Yes

**61. Program ProClean:**

Yes

**62. Program ProDrain:**

Yes

**63. Program ProEco:**

Yes

**64. Program ProLong:**

Yes

**65. Program ProPlates:**

Yes

**66. Program ProActive 5:**

Yes

**67. Program ProActive 7:**

Yes

**68. Program ProSteel:**

Yes

**69. Program ProSan:**

Yes

**70. Cross-section of conductors CU [mm<sup>2</sup>]:**

2

**71. Water supply connection:**

3/4"

**72. Diameter nominal:**

DN 50