

Convection oven STEAMBOX electric 10x GN 2/1 touch digital Automatic cleaning boiler 400 V		
Model	SAP Code	00011586
SDBB 1021 EAM	A group of articles - web	Convection machines
		 Steam type: Symbiotic - boiler and injection combination (patent) Number of GN / EN: 10 GN / EN size in device: GN 2/1 GN device depth: 65 Control type: Digital Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented) Advanced moisture adjustment: Supersteam - two steam saturation modes Delta T heat preparation: Yes Automatic preheating: Yes Multi level cooking: No Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011586	Loading	400 V / 3N - 50 Hz
Net Width [mm]	1120	Steam type	Symbiotic - boiler and injection combina- tion (patent)
Net Depth [mm]	845	Number of GN / EN	10
Net Height [mm]	1115	GN / EN size in device	GN 2/1
Net Weight [kg]	220.00	GN device depth	65
Power electric [kW]	28.300	Control type	Digital

Technical data sheet

Product benefits



Convection oven STEAMBOX electric 10x GN 2/1 touch digital Automatic cleaning boiler 400 V				
Model SAP Code		000115	86	
SDBB	3 1021 EAM	A group of articles - web	Convec	ction machines
1	A symbiotic steam general simultaneous use of direct inje maintenance of 100% humidit Digital display	ction and boiler,	and boiler, ts regulation 8 the only burner with a turbo pre -mixing gas with on the market the structure of the burner to V which prevents backfill and banging This design saves 30 % of gas compared to	
2 3	simple multi-line backlit displa cooking phases Weather system patented device for measuring time and in steam mode, the c	steam saturation in real	9	conventional burners Automatic washing integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler
4	Steam tuner a control element that enables saturation of steam in the cool cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed
5	Pass-through door the door is also built into the b while full control is retained fro enables the distribution of the and the kitchen	om the side of the cook	11	Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually
6	Adaptation for roasting c the chamber of the convectior baked fat, the machine is equi collecting fat	oven is designed to collect	12	External temperature probe temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe
7	A kit of two machines on connection kit allowing two m top of each other connects the connections, inle of the lower combi oven	achines to be placed on	13 14	Longitudinal insertion to GN penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts USB downloading service reports software upgrade recipe playback



Convection oven STEAMBOX elec	tric 10x GN 2/1 touch	digital Automatic cleaning boiler 400 V
Model	SAP Code	00011586
SDBB 1021 EAM	A group of articles - web	Convection machines
1. SAP Code: 00011586		14. Exterior color of the device: Stainless steel
2. Net Width [mm]: 1120		15. Adjustable feet: Yes
3. Net Depth [mm]: 845		16. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
4. Net Height [mm]: 1115		17. Stacking availability: Yes
5. Net Weight [kg]: 220.00		18. Control type: Digital
6. Gross Width [mm]: 1320		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
7. Gross depth [mm]: 1130		20. Steam type: Symbiotic - boiler and injection combination (patent)
8. Gross Height [mm]: 1240		21. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 230.00		22. Delta T heat preparation: Yes
10. Device type: Electric unit		23. Automatic preheating: Yes
11. Power electric [kW]: 28.300		24. Automatic cooling: Yes
12. Loading: 400 V / 3N - 50 Hz		25. Unified finishing of meals EasyService: No
13. Material: AISI 304		26. Night cooking: No

Technical parameters



Convection oven STEAMBOX	electric 10x GN 2/1 touch di	gital Automatic cleaning boiler 400 V
Model	SAP Code	00011586
SDBB 1021 EAM	A group of articles - web	Convection machines
27. Washing system: Closed - efficient use of water repeated pumping	and washing chemicals by	40. Distance between the layers [mm]: 70
28. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		41. Smoke-dry function: No
29. Multi level cooking:		42. Interior lighting:
No		Yes
30. Advanced moisture adjustment:		43. Low temperature heat treatment:
Supersteam - two steam saturation modes		Yes
31. Slow cooking: from 30 °C - the possibility of rising		44. Number of fans:
32. Fan stop:		45. Number of fan speeds:
Immediate when the door is opened		6
33. Lighting type:		46. Number of programs:
LED lighting in the doors, on both sides		99
34. Cavity material and shape:		47. USB port:
AISI 304, with rounded corners for easy cleaning		Yes, for uploading recipes and updating firmware
35. Reversible fan:		48. Door constitution:
Yes		Vented safety double glass, removable for easy cleaning
6. Sustaince box: Yes		49. Number of preset programs: 40
87. Heating element material:		50. Number of recipe steps:
Incoloy		9
88. Probe:		51. Minimum device temperature [°C]:
Optional		30
39. Shower:		52. Maximum device temperature [°C]:
volitelná		300



Convection oven STEAMBOX electric 10x GN 2/1 touch digital Automatic cleaning boiler 400 V			
Model	SAP Code	00011586	
SDBB 1021 EAM	A group of articles - web	Convection machines	
53. Device heating type: Combination of steam and hot air		58. Food regeneration: Yes	
54. HACCP: Yes		59. Cross-section of conductors CU [mm²]: 10	
55. Number of GN / EN: 10		60. Diameter nominal: DN 50	
56. GN / EN size in device: GN 2/1		61. Water supply connection: 3/4"	
57. GN device depth:			

65