Technical data sheet

Product features



STEAMBOX gas convection oven 10x GN 2/1 Automatic cleaning Direct steam				
Model	SAP Code	00008601		
STBD 1021 G	A group of articles - web	Convection machines		
		 Steam type: Injection Number of GN / EN: 10 GN / EN size in device: GN 2/1 GN device depth: 65 Control type: Touchscreen + butto Display size: 9" Humidity control: MeteoSystem - measurement of humidity in the of Advanced moisture adjustment: S saturation modes Delta T heat preparation: Yes Automatic preheating: Yes Multi level cooking: Drawer progr treatment for each dish separatel Door constitution: Vented safety of easy cleaning 	regulation based on direct chamber (patented) Supersteam - two steam am - control of heat y	
SAP Code	00008601	Type of gas	Natural Gas	
Net Width [mm]	1120	Steam type	Injection	
Net Depth [mm]	845	Number of GN / EN	10	
Net Height [mm]	1115	GN / EN size in device	GN 2/1	
Net Weight [kg]	250.00	GN device depth	65	
Power electric [kW]	0.800	Control type	Touchscreen + buttons	

9"

Loading

Power gas [kW]

Display size

230 V / 1N - 50 Hz

28.000

Technical data sheet

Product benefits



del		SAP Code	000086	01	
TBD 1021 G A group of articles - web		Convection machines			
L	Direct injection steam generation by spraying w elements directly in the chambe	eam generation by spraying water on the heating		8 Premix burner the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents backfill and banging	
2	Touch screen display simple intuitive control with uni all in Czech the possibility of using preset pr		9	This design saves 30 % of gas compared to conventional burners Automatic washing	
3	Weather system patented device for measuring s time and in steam mode, the on		3	integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler	
1	Steam tuner a control element that enables s saturation of steam in the cooki cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed	
5	Pass-through door the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen		11	Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually	
			10	External temperature probe	
5	Adaptation for roasting ch the chamber of the convection of baked fat, the machine is equip	oven is designed to collect	ЦZ	temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe	
7	A kit of two machines on t	•	13	Longitudinal insertion to GN penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts	
ľ	connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation of the lower combi oven		14	USB downloading service reports software upgrade	

Technical parameters



STEAMBOX gas convection oven 10)x GN 2/1 Automatic	cleaning Direct steam		
Model	SAP Code	00008601		
STBD 1021 G	A group of articles - web	Convection machines		
1. SAP Code: 00008601		14. Type of gas: Natural Gas		
2. Net Width [mm]: 1120		15. Material: AISI 304		
3. Net Depth [mm]: 845		16. Exterior color of the device: Stainless steel		
4. Net Height [mm]: 1115		17. Adjustable feet: Yes		
5. Net Weight [kg]: 250.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)		
6. Gross Width [mm]: 1320		19. Stacking availability: Yes		
7. Gross depth [mm]: 1130		20. Control type: Touchscreen + buttons		
8. Gross Height [mm]: 1240		21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)		
9. Gross Weight [kg]: 260.00		22. Steam type: Injection		
10. Device type: Gas unit		23. Chimney for moisture extraction: Yes		
11. Power electric [kW]: 0.800		24. Delayed start: Yes		
12. Loading: 230 V / 1N - 50 Hz		25. Display size: 9"		
13. Power gas [kW]: 28.000		26. Delta T heat preparation: Yes		

Technical parameters



STEAMBOX gas convection oven 10	x GN 2/1 Automatic cl	eaning Direct steam	
Model	SAP Code	00008601	
STBD 1021 G	A group of articles - web	Convection machines	
27. Automatic preheating: Yes		40. Sustaince box: Yes	
8. Automatic cooling: Yes		41. Probe: Yes	
29. Unified finishing of meals EasyService: Yes		42. Shower: Hand winder	
80. Night cooking: Yes		43. Distance between the layers [mm]: 70	
 Washing system: Closed - efficient use of water and washing chemicals by repeated pumping 		44. Smoke-dry function: Yes	
 Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets 		45. Interior lighting: Yes	
33. Multi level cooking: Drawer program - control of heat tre dish separately	atment for each	46. Low temperature heat treatment: Yes	
34. Advanced moisture adjustment: Supersteam - two steam saturation modes		47. Number of fans:	
85. Slow cooking: from 50 °C		48. Number of fan speeds: 6	
6. Fan stop: Immediate when the door is opened		49. Number of programs: 1000	
87. Lighting type: LED lighting in the doors, on both sides		50. USB port: Yes, for uploading recipes and updating firmware	
88. Cavity material and shape: AISI 304, with rounded corners for easy cleaning		51. Door constitution: Vented safety double glass, removable for easy cleaning	
39. Reversible fan: Yes		52. Number of preset programs: 100	

Technical data sheet

Technical parameters



STEAMBOX gas convection oven 10x GN 2/1 Automatic cleaning Direct steam				
Model	SAP Code	00008601		
STBD 1021 G	A group of articles - web	Convection machines		
53. Number of recipe steps: 9		59. GN / EN size in device: GN 2/1		
54. Minimum device temperature [°C]: 50		60. GN device depth: 65		
55. Maximum device temperature [°C]: 300		61. Food regeneration: Yes		
56. Device heating type: Combination of steam and hot air		62. Connection to a ball valve: 1/2		
57. HACCP: Yes		63. Diameter nominal: DN 50		
58. Number of GN / EN: 10		64. Water supply connection: 3/4"		