

# Technical data sheet

## Product features



### Pasta cooker electric automatic water loading


|              |                                  |                               |
|--------------|----------------------------------|-------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00013571                      |
| CPAD-64ET    | <b>A group of articles - web</b> | Pasta cookers and Bain Marine |



- Basin volume [l]: 25
- Water inlet: automatic valve operated by button
- Drain type: Through the substructure with connection to waste
- Drain: Yes
- Material: Stainless steel
- Protection of controls: IPX5
- Maximum device temperature [°C]: 110
- Number of baskets: 0

|                            |          |                               |                    |
|----------------------------|----------|-------------------------------|--------------------|
| <b>SAP Code</b>            | 00013571 | <b>Loading</b>                | 400 V / 3N - 50 Hz |
| <b>Net Width [mm]</b>      | 400      | <b>Basin volume [l]</b>       | 25                 |
| <b>Net Depth [mm]</b>      | 600      | <b>Number of baskets</b>      | 0                  |
| <b>Net Height [mm]</b>     | 510      | <b>Number of GN / EN</b>      | 1                  |
| <b>Net Weight [kg]</b>     | 15.00    | <b>GN / EN size in device</b> | GN 2/3             |
| <b>Power electric [kW]</b> | 7.800    | <b>GN device depth</b>        | 220                |

# Technical drawing



# Technical data sheet

## Technical parameters



### Pasta cooker electric automatic water loading

|              |                                  |                               |
|--------------|----------------------------------|-------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00013571                      |
| CPAD-64ET    | <b>A group of articles - web</b> | Pasta cookers and Bain Marine |

**1. SAP Code:**

00013571

**2. Net Width [mm]:**

400

**3. Net Depth [mm]:**

600

**4. Net Height [mm]:**

510

**5. Net Weight [kg]:**

15.00

**6. Gross Width [mm]:**

630

**7. Gross depth [mm]:**

690

**8. Gross Height [mm]:**

540

**9. Gross Weight [kg]:**

22.00

**10. Device type:**

Electric unit

**11. Construction type of device:**

Drop-in

**12. Power electric [kW]:**

7.800

**13. Loading:**

400 V / 3N - 50 Hz

**14. Protection of controls:**

IPX5

**15. Material:**

Stainless steel

**16. Indicators:**

operation and warm-up

**17. Drain valve diameter:**

1"

**18. Worktop type:**

Molded - comfortable cleaning maintenance

**19. Basin volume [l]:**

25

**20. Basin dimensions [mm x mm x mm]:**

305 x 335 x 327

**21. Maximum device temperature [°C]:**

110

**22. Minimum device temperature [°C]:**

30

**23. Power control type:**

knob control

**24. Service accessibility:**

Trough the frontal panel

**25. Safety element:**

safety thermostat  
microswitch preventing the device from running when there is no water in the bath  
overflow channel

**26. Safety thermostat:**

Yes

# Technical data sheet

## Technical parameters



### Pasta cooker electric automatic water loading

|              |                                  |                               |
|--------------|----------------------------------|-------------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00013571                      |
| CPAD-64ET    | <b>A group of articles - web</b> | Pasta cookers and Bain Marine |

**27. Additional information:**

basket not included - baskets in different sizes can be purchased

**28. Number of baskets:**

0

**29. Number of basins:**

1

**30. Basin material:**

AISI 316 - Stainless steel highly resistant to salt water

**31. Heating element construction:**

Swivel

**32. Water inlet:**

automatic valve operated by button

**33. Drain type:**

Through the substructure with connection to waste

**34. Drain:**

Yes

**35. Number of GN / EN:**

1

**36. GN / EN size in device:**

GN 2/3

**37. GN device depth:**

220

**38. Drain connection:**

Yes

**39. Heating location:**

Inside the tank

**40. Cross-section of conductors CU [mm²]:**

1,5