



STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing		
Model	SAP Code	00038363
STMB 0611 E	A group of articles - web	Convection machines




- Steam type: Symbiotic boiler and injection combination (patent)
- Number of GN / EN: 6
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Touchscreen
- Display size: 10"
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Steamtuner 5-stage system of setting steam saturation by controlled combination of production by boiler or injection
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Odvětrávané bezpečnostní trojité sklo, rozebiratelné pro snadné čištění


SAP Code	00038363	Steam type	Symbiotic - boiler and injection combina-tion (patent)
Net Width [mm]	860	Number of GN / EN	6
Net Depth [mm]	795	GN / EN size in device	GN 1/1
Net Height [mm]	835	GN device depth	65
Net Weight [kg]	107.00	Control type	Touchscreen
Power electric [kW]	11.400	Display size	10"
Loading	400 V / 3N - 50 Hz		




Technical drawing

STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing		
Model	SAP Code	00038363
STMB 0611 E	A group of articles - web	Convection machines











STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing		
Model	SAP Code	00038363
STMB 0611 E	A group of	Convection machines

Triple glass door as standard better thermal insulation, less frequency

better thermal insulation, less frequent reheating, safer operation due to lower outer glass temperature, less radiant heat, less heat leakage, lower load on electronics and mechanical parts

Clear 10" touch screen corresponding to other RM line devices

simple intuitive operation using images and visualizations, the same intuitive operation as on other digital devices in the RM line

Smart cooking

Predefined basic programs for easy control with just a few touches

Symbiotic steam generation system

simultaneous use of "direct injection" and boiler, maintaining 100% humidity, or its regulation

\_\_ | Self-winding shower

vacuum probe

drum reel integrated in the combi oven body the shower is inaccessible after closing the door

Fan six-speed, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect distribution of steam without loss of its saturation, its operation is controlled by program or manually

option to choose from a single or multi-point probe or

**External temperature probe**temperature probe placed outside the cooking space

Longitudinal drawers for GN

drawers placed at the "depth" of the machine option to replace with drawers for 600x400 trays

USB

downloading service reports upgrade software playback recipes

Automatic washing

integrated chamber washing system option to use liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro-boiler

Meteo system

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

Kit of two machines on top of each other

interconnection kit allowing two machines to be stacked on top of each other

interconnects connections, inlets, wastes and ventilation of the lower combi oven

Adjustment for roasting chicken

The combi oven chamber is designed to collect baked-on fat, the machine is equipped with a fat collection container



#### Technical parameters

STEAMBOX electric convector 6x	GN 1/1 boiler touch c	olored auto. washing
Model	SAP Code	00038363
STMB 0611 E	A group of articles - web	Convection machines
<b>1. SAP Code:</b> 00038363		<b>14. Exterior color of the device:</b> Stainless steel
<b>2. Net Width [mm]:</b> 860		<b>15. Adjustable feet:</b> Yes
<b>3. Net Depth [mm]:</b> 795		<b>16. Humidity control:</b> MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
4. Net Height [mm]: 835		17. Stacking availability: Yes
5. Net Weight [kg]: 107.00		18. Control type: Touchscreen
<b>6. Gross Width [mm]:</b> 955		<b>19. Additional information:</b> possibility of reverse door opening - handle on the right side (must be specified when ordering)
7. Gross depth [mm]: 920		20. Steam type: Symbiotic - boiler and injection combination (patent)
8. Gross Height [mm]:		<b>21. Chimney for moisture extraction:</b> Yes
9. Gross Weight [kg]: 128.00		<b>22. Delayed start:</b> Yes
10. Device type: Electric unit		23. Display size:
<b>11. Power electric [kW]:</b> 11.400		24. Delta T heat preparation: Yes
<b>12. Loading:</b> 400 V / 3N - 50 Hz		25. Automatic preheating: Yes
13. Material:		26. Automatic cooling:

AISI 304

Yes



#### Technical parameters

STEAMBOX electric convector 6x 0	6N 1/1 boiler touch colo	red auto. washing
Model	SAP Code	00038363
STMB 0611 E	A group of articles - web	Convection machines
<b>27. Cold smoke-dry function:</b> Yes		<b>39. Sustaince box:</b> Yes
28. Unified finishing of meals EasyS	Service:	<b>40. Heating element material:</b> Incoloy
29. Night cooking: Yes		<b>41. Probe:</b> Yes
30. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping		<b>42. Shower:</b> Hand winder
<b>31. Detergent type:</b> Liquid washing detergent + liquid r washing tablets	inse aid/vinegar or	<b>43. Distance between the layers [mm]:</b> 70
<b>32. Multi level cooking:</b> Drawer program - control of heat tr dish separately	eatment for each	<b>44. Smoke-dry function:</b> Yes
<b>33. Advanced moisture adjustment:</b> Steamtuner - 5-stage system of setting steam saturation by controlled combination of production by boiler or injection		<b>45. Interior lighting:</b> Yes
<b>34. Slow cooking:</b> from 30 °C - the possibility of rising		<b>46. Low temperature heat treatment:</b> Yes
<b>35. Fan stop:</b> Immediate when the door is opened	ed	<b>47. Number of fans:</b>
<b>36. Lighting type:</b> LED lighting in the doors, on both s	ides	<b>48. Number of fan speeds:</b>
<b>37. Cavity material and shape:</b> AISI 304, with rounded corners for e	easy cleaning	<b>49. Number of programs:</b> 1000

38. Reversible fan:

Yes

50. USB port:

Yes, for uploading recipes and updating firmware



#### Technical parameters

STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing			
Model	SAP Code	00038363	
STMB 0611 E	A group of articles - web	Convection machines	
<b>51. Door constitution:</b> Odvětrávané bezpečnostní trojité s snadné čištění	sklo, rozebiratelné pro	<b>58. Number of GN / EN:</b>	
<b>52. Number of preset programs:</b> 100		<b>59. GN / EN size in device:</b> GN 1/1	
<b>53.</b> Number of recipe steps:		<b>60. GN device depth:</b> 65	
<b>54.</b> Minimum device temperature [°C]: 30		<b>61. Food regeneration:</b> Yes	
<b>55.</b> Maximum device temperature [°C]: 300		62. Cross-section of conductors CU [mm²]:	_
<b>56. Device heating type:</b> Combination of steam and hot air		<b>63. Diameter nominal:</b> DN 50	
57. HACCP:		64. Water supply connection:	_

3/4"

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

Yes