

Technical data sheet

Product features



650 W blender motor

Model	SAP Code	00013286
PMF M65	A group of articles - web	Accessories



– Material: ABS plastic

Technical data sheet

Technical drawing



650 W blender motor

Model	SAP Code	00013286
PMF M65	A group of articles - web	Accessories

Technical data sheet

Product benefits



650 W blender motor

Model	SAP Code	00013286
PMF M65	A group of articles - web	Accessories

1

Powerful engine

strength and speed, overload resistance, long life

- comfort for the operator, time saving

2

Variable speed

the possibility of processing different types of food

- multiple devices can be represented

3

Engine only

option to choose accessories as needed

- cost savings no need to buy what I don't need or, on the other hand, additional machines

4

Ergonomic handle

easy and convenient to use

- higher security
- less fatigue during use

5

Stainless motor cover

easy and convenient to use

- long service life

6

Bayonet clutch with star shape

perfect torque transmission
resistance to breaking out

- perfect food processing
- durability

Technical data sheet

Technical parameters



650 W blender motor

Model	SAP Code	00013286
PMF M65	A group of articles - web	Accessories

1. SAP Code:

00013286

2. Net Width [mm]:

130

3. Net Depth [mm]:

130

4. Net Height [mm]:

400

5. Net Weight [kg]:

0.40

6. Gross Width [mm]:

190

7. Gross depth [mm]:

170

8. Gross Height [mm]:

440

9. Gross Weight [kg]:

0.60

10. Material:

ABS plastic

11. Gasket:

Yes

12. Additional information:

interchangeable whisking, mixing, homogenising and emulsifying attachments
control board with SRS system for power and speed stabilisation

13. Connections material:

Polymer

14. Control type:

Digital

15. Engine protection:

overheating protection

16. Ergonomic handle:

Yes

17. Loading:

230 V / 1N - 50 Hz

18. Main switch:

Yes

19. Number of speeds of device:

9

20. Power electric [kW]:

0.650

21. Recommended accessories:

00013299;00013310;00013291;00013313;00013314;00013315;00013316;00013317;00013318;00013319

22. Safety element:

thermal overload protection

23. Mixing speed [rpm]:

13000

24. Whipping speed [rpm]:

2000 - 9000

25. Way of tool mounting:

Bayonet coupling, double, sliding nut

26. Cross-section of conductors CU [mm²]:

0,5