

Technical data sheet

Product features



Bain marie stationary electric GN 4-1/1 controllers on shorter side with rack

Model	SAP Code	00005945
BMSK 4120	A group of articles - web	Pasta cookers and Bain Marine



- Drain: Yes
- Material: AISI 304 top plate, AISI 430 cladding
- Protection of controls: IPX4
- Maximum device temperature [°C]: 90
- Device properties: Warmed

SAP Code	00005945	Power electric [kW]	2.800
Net Width [mm]	598	Loading	230 V / 1N - 50 Hz
Net Depth [mm]	1601	Number of GN / EN	4
Net Height [mm]	905	GN / EN size in device	GN 1/1
Net Weight [kg]	68.00	GN device depth	200


Technical data sheet

Technical drawing



Bain marie stationary electric GN 4-1/1 controllers on shorter side with rack

Model	SAP Code	00005945
BMSK 4120	A group of articles - web	Pasta cookers and Bain Marine



Technical data sheet

Product benefits



Bain marie stationary electric GN 4-1/1 controllers on shorter side with rack

Model	SAP Code	00005945
BMSK 4120	A group of articles - web	Pasta cookers and Bain Marine

1

Deep-draft bathtubs

basins without sharp transitions, edges and corners

2

Controlling each bath separately

variability of use

3

All-stainless steel construction

harmless to health for contact with food
robustness

4

Drain valve under the bathtub

safer placement of the drain valve

Technical data sheet

Technical parameters



Bain marie stationary electric GN 4-1/1 controllers on shorter side with rack

Model	SAP Code	00005945
BMSK 4120	A group of articles - web	Pasta cookers and Bain Marine

1. SAP Code:

00005945

2. Net Width [mm]:

598

3. Net Depth [mm]:

1601

4. Net Height [mm]:

905

5. Net Weight [kg]:

68.00

6. Gross Width [mm]:

730

7. Gross depth [mm]:

1700

8. Gross Height [mm]:

1010

9. Gross Weight [kg]:

70.00

10. Device type:

Electric unit

11. Construction type of device:

Stationary

12. Power electric [kW]:

2.800

13. Loading:

230 V / 1N - 50 Hz

14. Protection of controls:

IPX4

15. Exterior color of the device:

Stainless steel

16. Material:

AISI 304 top plate, AISI 430 cladding

17. Maximum device temperature [°C]:

90

18. Minimum device temperature [°C]:

30

19. Drain:

Yes

20. Number of GN / EN:

4

21. GN / EN size in device:

GN 1/1

22. GN device depth:

200

23. Cross-section of conductors CU [mm²]:

0,75

24. Device properties:

Warmed