

Technical data sheet

Product features



Multifunctional kitchen appliance INFINITY 8x GN 1/1

Model	SAP Code	00010705
INFINITY 0811	A group of articles - web	Šokery a multifunkční zařízení



- Shock cooling cycle kg / min (+3 ° C): 35/90
- Shock freeze cycle kg / min (-18 ° C): 25/240
- Maximum device temperature [°C]: -40
- Probe: 4-points
- Insulation thickness [mm]: 60
- Control type: Digital
- Display size: 9"
- User programmable cycles: Yes, with save options
- Defrosting cycle: Yes

SAP Code	00010705	Number of GN / EN	8
Net Width [mm]	790	GN / EN size in device	GN 1/1
Net Depth [mm]	839	GN device depth	65
Net Height [mm]	1322	Shock cooling cycle kg / min (+3 ° C)	35/90
Net Weight [kg]	126.00	Shock freeze cycle kg / min (-18 ° C)	25/240
Power electric [kW]	0.900	Control type	Digital
Loading	230 V / 1N - 50 Hz		

Technical data sheet

Technical drawing



Multifunctional kitchen appliance INFINITY 8x GN 1/1

Model	SAP Code	00010705
INFINITY 0811	A group of articles - web	Šokery a multifunkční zařízení



Technical data sheet

Product benefits



Multifunctional kitchen appliance INFINITY 8x GN 1/1

Model	SAP Code	00010705
INFINITY 0811	A group of articles - web	Šokery a multifunkční zařízení

1

6 in 1

can replace 6 devices (fridge, freezer, shocker, hotbox, kitchen, oven)

- saves space, time, energy and the cost of additional equipment due to the enormous variability

2

Stainless steel body and interior

endurance
hygiene

- thanks to the all-stainless steel construction it is very easy to maintain and thus saves costs

3

Monitoring of HACCP parameters

easy registration of all necessary parameters

- hassle-free proof of proper food handling in the event of an inspection

4

Preset cycles

very simple and intuitive operation

- operation can be handled by less qualified operators

5

Slow cooking

better taste
less weight loss during cooking

- saves costs due to less weight loss

6

Multipoint probe

precise monitoring of the cooling/freezing/
cooking temperature

- the probe makes it easier to ensure food safety
- saves energy and time due to the end of cooling/
freezing/cooking when temperature is reached

7

Thawing

readiness of frozen food for processing on time

- time saving
- controlled food handling

8

Cooking during the night

the possibility to preset entire program cycles and run them overnight unattended

- saving equipment capacity during the day
- saving of human capacity and time due to unattended operation of the equipment overnight

Technical data sheet

Technical parameters



Multifunctional kitchen appliance INFINITY 8x GN 1/1

Model	SAP Code	00010705
INFINITY 0811	A group of articles - web	Šokery a multifunkční zařízení

1. SAP Code:

00010705

2. Net Width [mm]:

790

3. Net Depth [mm]:

839

4. Net Height [mm]:

1322

5. Net Weight [kg]:

126.00

6. Gross Width [mm]:

846

7. Gross depth [mm]:

860

8. Gross Height [mm]:

1450

9. Gross Weight [kg]:

145.70

10. Device type:

Electric unit

11. Material:

AISI 304

12. Exterior color of the device:

Stainless steel

13. Power electric [kW]:

0.900

14. Loading:

230 V / 1N - 50 Hz

15. Control type:

Digital

16. Display size:

9"

17. Refrigerant:

R452a

18. Number of GN / EN:

8

19. GN / EN size in device:

GN 1/1

20. GN device depth:

65

21. Maximum device temperature [°C]:

-40

22. Shock freeze cycle kg / min (-18 ° C):

25/240

23. Shock cooling cycle kg / min (+3 ° C):

35/90

24. Insulation thickness [mm]:

60

25. Long-term cooling function:

Yes

26. Longterm freezing function:

Yes

27. Probe:

4-points

28. Self-diagnostics:

Yes

Technical data sheet

Technical parameters



Multifunctional kitchen appliance INFINITY 8x GN 1/1

Model	SAP Code	00010705
INFINITY 0811	A group of articles - web	Šokery a multifunkční zařízení

29. Low temperature heat treatment:

Yes

30. Low temperature cooking span [°C]:

52-85

31. Defrosting cycle:

Yes

32. User programmable cycles:

Yes, with save options

33. USB port:

Yes, for HACCP and firmware update

34. Castors:

Optional

35. Real time monitoring parameters:

Energy consumption, Chamber temperature, Probe temperature, Graph with the course of temperature and consumption

36. Cross-section of conductors CU [mm²]:

0,5