Technical data sheet

168.00

15.700

400 V / 3N - 50 Hz

Product features



Steambox steamer electric 10x GN 1/1 Automatic cleaning Direct steam 400 V			
Model	SAP Code	00008595	
STBD 1011 E	A group of articles - web	Convection machines	
		 Steam type: Injection Number of GN / EN: 10 GN / EN size in device: GN 1/1 GN device depth: 65 Control type: Touchscreen + butto Display size: 9" Humidity control: MeteoSystem - measurement of humidity in the of Advanced moisture adjustment: Saturation modes Delta T heat preparation: Yes Automatic preheating: Yes Multi level cooking: Drawer progratication separatel Door constitution: Vented safety of easy cleaning 	regulation based on direct chamber (patented) Supersteam - two steam am - control of heat y
SAP Code	00008595	Steam type	Injection
Net Width [mm]	860	Number of GN / EN	10
Net Depth [mm]	795	GN / EN size in device	GN 1/1
Net Height [mm]	1115	GN device depth	65

Touchscreen + buttons

9"

Net Weight [kg]

Loading

Power electric [kW]

Control type

Display size

Technical data sheet

Product benefits



del		SAP Code	00008595	
TBD 1011 E A group of articles - web			Convection machines	
L	Direct injection steam generation by spraying w elements directly in the chambe		8	Premix burner the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents backfill and banging
2	Touch screen display simple intuitive control with un all in Czech the possibility of using preset p			This design saves 30 % of gas compared to conventional burners
3	Weather system patented device for measuring s time and in steam mode, the or		9	integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler
1	Steam tuner a control element that enables saturation of steam in the cooki cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed
5	Pass-through door the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen		11	Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually
5	Adaptation for roasting ch the chamber of the convection baked fat, the machine is equip	oven is designed to collect	12	External temperature probe temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe
7	collecting fat A kit of two machines on top of each other connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation of the lower combi oven		13 14	Longitudinal insertion to GN penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts USB downloading service reports software upgrade



Steambox steamer electric 10x G	N 1/1 Automatic clean	ning Direct steam 400 V	
Model	SAP Code	00008595	
STBD 1011 E	A group of articles - web	Convection machines	
1. SAP Code: 00008595		14. Exterior color of the device: Stainless steel	
2. Net Width [mm]: 860		15. Adjustable feet: Yes	
3. Net Depth [mm]: 795		16. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)	
4. Net Height [mm]: 1115		17. Stacking availability: Yes	
5. Net Weight [kg]: 168.00		18. Control type: Touchscreen + buttons	
6. Gross Width [mm]: 955		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)	
7. Gross depth [mm]: 920		20. Steam type: Injection	
8. Gross Height [mm]: 1240		21. Chimney for moisture extraction: Yes	
9. Gross Weight [kg]: 178.00		22. Delayed start: Yes	
10. Device type: Electric unit		23. Display size: 9"	
11. Power electric [kW]: 15.700		24. Delta T heat preparation: Yes	
12. Loading: 400 V / 3N - 50 Hz		25. Automatic preheating: Yes	
13. Material: AISI 304		26. Automatic cooling: Yes	

Technical parameters



Steambox steamer electric 10x GN 1/1 Automatic cleaning Direct steam 400 V				
Model	SAP Code	00008595		
STBD 1011 E	A group of articles - web	Convection machines		
27. Cold smoke-dry function:		40. Heating element material:		
Yes		Incoloy		
28. Unified finishing of meals EasyService:		41. Probe:		
Yes		Yes		
29. Night cooking:		42. Shower:		
Yes		Hand winder		
30. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping		43. Distance between the layers [mm]: 70		
31. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		44. Smoke-dry function: Yes		
32. Multi level cooking: Drawer program - control of heat tr dish separately	eatment for each	45. Interior lighting: Yes		
33. Advanced moisture adjustment:		46. Low temperature heat treatment:		
Supersteam - two steam saturation modes		Yes		
34. Slow cooking: from 50 °C		47. Number of fans:		
35. Fan stop:		48. Number of fan speeds:		
Immediate when the door is opened		6		
36. Lighting type:		49. Number of programs:		
LED lighting in the doors, on both sides		1000		
37. Cavity material and shape:		50. USB port:		
AISI 304, with rounded corners for easy cleaning		Yes, for uploading recipes and updating firmware		
38. Reversible fan:		51. Door constitution:		
Yes		Vented safety double glass, removable for easy cleaning		
39. Sustaince box: Yes		52. Number of preset programs: 100		

Technical data sheet

Technical parameters



Steambox steamer electric 10x GN 1/1 Automatic cleaning Direct steam 400 V				
Model	SAP Code	00008595		
STBD 1011 E	A group of articles - web	Convection machines		
53. Number of recipe steps: 9		59. GN / EN size in device: GN 1/1		
54. Minimum device temperature [°C]: 50		60. GN device depth: 65		
55. Maximum device temperature [°C]: 300		61. Food regeneration: Yes		
56. Device heating type: Combination of steam and hot air		62. Cross-section of conductors CU [mm²]:		
57. HACCP: Yes		63. Diameter nominal: DN 50		
58. Number of GN / EN: 10		64. Water supply connection: 3/4"		