

#### Product features

Combi convection steam oven STEAMBOX electric 6x GN 1/1 touch screen automatic cleaning boiler 400 V		
Model	SAP Code	00010973
SDBB 0611 EAM	A group of articles - web	Convection machines
		<ul> <li>Steam type: Symbiotic - boiler and injection combination (patent)</li> <li>Number of GN / EN: 6</li> <li>GN / EN size in device: GN 1/1</li> <li>GN device depth: 65</li> <li>Control type: Digital</li> <li>Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)</li> <li>Advanced moisture adjustment: Supersteam - two steam saturation modes</li> <li>Delta T heat preparation: Yes</li> <li>Automatic preheating: Yes</li> <li>Multi level cooking: No</li> <li>Door constitution: Vented safety double glass, removable for easy cleaning</li> </ul>

SAP Code	00010973	Loading	400 V / 3N - 50 Hz
Net Width [mm]	860	Steam type	Symbiotic - boiler and injection combination (patent)
Net Depth [mm]	795	Number of GN / EN	6
Net Height [mm]	835	GN / EN size in device	GN 1/1
Net Weight [kg]	132.00	GN device depth	65
Power electric [kW]	11.400	Control type	Digital





Combi	convection steam oven ST	EAMBOX electric 6x GN 1/1	l touch sc	reen automatic cleaning boiler 400 V
Model		SAP Code	000109	73
SDBE	3 0611 EAM	A group of articles - web	Convec	tion machines
1	maintenance of 100% humidity, or its regulation  on the market the structure of the burner to V which p		the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents	
2	<b>Digital display</b> simple multi-line backlit displa cooking phases	ay of 99 programs with 9		backfill and banging This design saves 30 % of gas compared to conventional burners
3	Weather system patented device for measuring time and in steam mode, the c		9	Automatic washing integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler
4	Steam tuner a control element that enables saturation of steam in the cool cooking process		10	Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed
5	Pass-through door the door is also built into the built full control is retained from the and the kitchen	om the side of the cook	11	Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually
6	Adaptation for roasting of the chamber of the convection baked fat, the machine is equi collecting fat	oven is designed to collect	12	<b>External temperature probe</b> temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe
7	A kit of two machines on connection kit allowing two m top of each other	achines to be placed on	13	<b>Longitudinal insertion to GN</b> penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts
	connects the connections, inle of the lower combi oven	ets, wastes and ventilation	14	downloading service reports software upgrade recipe playback



### Technical parameters

Combi convection steam oven STEAMBOX electric 6x GN 1/1 touch screen automatic cleaning boiler 400 V		
Model	SAP Code	00010973
SDBB 0611 EAM	A group of articles - web	Convection machines
<b>1. SAP Code:</b> 00010973		<b>14. Exterior color of the device:</b> Stainless steel
<b>2. Net Width [mm]:</b> 860		<b>15. Adjustable feet:</b> Yes
<b>3. Net Depth [mm]:</b> 795		<b>16. Humidity control:</b> MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
4. Net Height [mm]: 835		17. Stacking availability: Yes
5. Net Weight [kg]: 132.00		18. Control type: Digital
<b>6. Gross Width [mm]:</b> 860		<b>19. Additional information:</b> possibility of reverse door opening - handle on the right side (must be specified when ordering)
7. Gross depth [mm]: 920		20. Steam type: Symbiotic - boiler and injection combination (patent)
8. Gross Height [mm]: 1020		21. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 142.00		<b>22. Delta T heat preparation:</b> Yes
10. Device type: Electric unit		23. Automatic preheating: Yes
11. Power electric [kW]: 11.400		24. Automatic cooling: Yes
<b>12. Loading:</b> 400 V / 3N - 50 Hz		25. Unified finishing of meals EasyService:
13. Material: AISI 304		26. Night cooking:



#### Technical parameters

Combi convection steam oven ST	EAMBOX electric 6x GN	1/1 touch screen automatic cleaning boiler 400 V	
Model	SAP Code	00010973	
SDBB 0611 EAM	A group of articles - web	Convection machines	
<b>27. Washing system:</b> Closed - efficient use of water and repeated pumping	washing chemicals by	<b>40. Distance between the layers [mm]:</b> 70	
28. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		<b>41. Smoke-dry function:</b> No	
29. Multi level cooking:		<b>42. Interior lighting:</b> Yes	
30. Advanced moisture adjustment: Supersteam - two steam saturation modes		<b>43. Low temperature heat treatment:</b> Yes	
<b>31. Slow cooking:</b> from 30 °C - the possibility of rising		44. Number of fans:	
32. Fan stop: Immediate when the door is opened		<b>45. Number of fan speeds:</b>	
<b>33. Lighting type:</b> LED lighting in the doors, on both	sides	<b>46. Number of programs:</b> 99	
<b>34. Cavity material and shape:</b> AISI 304, with rounded corners for easy cleaning		<b>47. USB port:</b> Yes, for uploading recipes and updating firmware	
<b>35. Reversible fan:</b> Yes		<b>48. Door constitution:</b> Vented safety double glass, removable for easy cleaning	
<b>36. Sustaince box:</b> Yes		<b>49. Number of preset programs:</b> 40	
37. Heating element material: Incoloy		<b>50. Number of recipe steps:</b> 9	
38. Probe: Optional		<b>51. Minimum device temperature [°C]:</b> 30	
<b>39. Shower:</b> volitelná		<b>52. Maximum device temperature [°C]:</b> 300	



### Technical parameters

Combi convection steam oven STEAMBOX electric 6x GN 1/1 touch screen automatic cleaning boiler 400 V		
Model	SAP Code	00010973
SDBB 0611 EAM	A group of articles - web	Convection machines
<b>53. Device heating type:</b> Combination of steam and hot air		<b>58. Food regeneration:</b> Yes
54. HACCP: Yes		59. Cross-section of conductors CU [mm²]:
55. Number of GN / EN:		<b>60. Diameter nominal:</b> DN 50
<b>56. GN / EN size in device:</b> GN 1/1		<b>61. Water supply connection:</b> 3/4"

57. GN device depth:

65