

Technical data sheet

Product features



Cooling tabletop electric GN1/1, 3x 1/2 drawers, without rim, stainless steel 230V OOP

Model	SAP Code	00019458
SCH 3D-6Z DH	A group of articles - web	Cooling and freezing tables



- Material: Stainless steel
- GN / EN size in device: GN 1/1
- Number of drawers: 6
- Control type: Digital
- Minimum device temperature [°C]: -2
- Maximum device temperature [°C]: 8
- Max ambient temperature [°C]: 43
- Insulation thickness [mm]: 70
- Unit: Right

SAP Code	00019458	Loading	230 V / 1N - 50 Hz
Net Width [mm]	1880	Number of drawers	6
Net Depth [mm]	700	GN / EN size in device	GN 1/1
Net Height [mm]	850	Minimum device temperature [°C]	-2
Net Weight [kg]	140.00	Maximum device temperature [°C]	8
Power electric [kW]	0.380	Refrigerant	R290

Technical data sheet

Technical drawing



Cooling tabletop electric GN1/1, 3x 1/2 drawers, without rim, stainless steel 230V OOP

Model	SAP Code	00019458
SCH 3D-6Z DH	A group of articles - web	Cooling and freezing tables

Technical data sheet

Technical parameters



Cooling tabletop electric GN1/1, 3x 1/2 drawers, without rim, stainless steel 230V OOP

Model	SAP Code	00019458
SCH 3D-6Z DH	A group of articles - web	Cooling and freezing tables

1. SAP Code:

00019458

2. Net Width [mm]:

1880

3. Net Depth [mm]:

700

4. Net Height [mm]:

850

5. Net Weight [kg]:

140.00

6. Gross Width [mm]:

1950

7. Gross depth [mm]:

750

8. Gross Height [mm]:

900

9. Gross Weight [kg]:

160.00

10. Device type:

Electric unit

11. Power electric [kW]:

0.380

12. Loading:

230 V / 1N - 50 Hz

13. Refrigerant:

R290

14. Material:

Stainless steel

15. Max ambient temperature [°C]:

43

16. Device properties 2:

Cooling

17. GN / EN size in device:

GN 1/1

18. Adjustable feet:

Yes

19. Pizza design:

No

20. Insulation thickness [mm]:

70

21. Number of drawers:

6

22. Unit:

Right

23. Control type:

Digital

24. Minimum device temperature [°C]:

-2

25. Maximum device temperature [°C]:

8

26. Gross Volume [m3]:

1.316

27. Net Volume [m3]:

1.119

28. Cross-section of conductors CU [mm²]:

0,5