

Technical data sheet

Product features



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD ProSmart soft touch
- Number of programs: 4
- Number of skin: 2
- Maximal rack feed [racks/h]: 200
- Door clear height [mm]: 450
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 0,8 - 1,4
- Washing cycle time [s/basket]: 18 - 37
- Detergent and rinse pump system: Accurate dosing with a peristaltic pump
- Wash pump type: DuoFlow
- Detergent dispenser: Yes
- Rinse aid dispenser: Yes

SAP Code	00010033	Boiler power [kW]	9.500
Net Width [mm]	2001	Basin volume [l]	70
Net Depth [mm]	813	Tank power [kW]	10.500
Net Height [mm]	1615	Water consumption of the washing cycle [l/basket]	0,8 - 1,4
Net Weight [kg]	193.00	Washing cycle time [s/basket]	18 - 37
Power electric [kW]	23.700	Maximal rack feed [racks/h]	200
Loading	400 V / 3N - 50 Hz	Door clear height [mm]	450
Boiler capacity [l]	17.00	Rack size [mm]	500 x 500


Technical data sheet

Technical drawing



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers



Technical data sheet

Product benefits



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers

1

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2

LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

3

Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

4

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

5

Energy saving

Energy Saving energy saving system due to lowering the temperature of the boiler

- cost saving

6

Protection of fragile dishes

softStart system of gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

7

Possibility of recovery

saving up to 40% of boiler energy
improves the comfort environment of the workplace
environment without steam
saves water

- saving on energy and water costs; environmentally friendly system; safe system; pleasant workplace

8

Fast heating

Performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

9

Air break tank

the open system of the boiler rinse, in cooperation with the rinse pump, ensures a constant pressure and temperature of the rinse

- possibility to use in HACCP systems water temperature suitable for sterilization

10

Sliding system

a sliding system that moves the baskets through individual washing zones, the possibility to connect the drive to automatic tables

- quick distribution of dirty dishes

Technical data sheet

Technical parameters



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers

1. SAP Code:

00010033

2. Net Width [mm]:

2001

3. Net Depth [mm]:

813

4. Net Height [mm]:

1615

5. Net Weight [kg]:

193.00

6. Gross Width [mm]:

2100

7. Gross depth [mm]:

920

8. Gross Height [mm]:

1850

9. Gross Weight [kg]:

230.00

10. Device type:

Electric unit

11. Control type:

Digital

12. Material:

AISI 304

13. Power electric [kW]:

23.700

14. Loading:

400 V / 3N - 50 Hz

15. Additional information:**16. Rack size [mm]:**

500 x 500

17. Number of programs:

4

18. Opening of device:

Retractable up

19. Door clear height [mm]:

450

20. Inlet pressure [bar]:

1-4

21. Adjustable feet:

Yes

22. Number of skin:

2

23. Modular construction:

Yes

24. Pre-wash module:

No

25. Maximal rack feed [racks/h]:

200

26. Self-cleaning cycle:

No

27. Boiler capacity [l]:

17.00

28. Boiler power [kW]:

9.500

Technical data sheet

Technical parameters



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers

29. Basin volume [l]:

70

30. Tank power [kW]:

10.500

31. Number of washing arms:

5

32. Number of rinsing arms:

6

33. Washing arm type:

Firm

34. Washing arm material:

Stainless steel

35. Atmospheric boiler with rinse pump:

Yes

36. Rinsing arm type:

Firm

37. Rinsing arm material:

Stainless steel

38. Deep drawn tank:

Yes

39. Rack support:

welded

40. Tank surface strainers:

stainless steel

41. Boiler thermostat adjust:

Yes

42. Rack feed capacity:

95-150-200

43. Detergent and rinse pump system:

Accurate dosing with a peristaltic pump

44. Hot water electric valve:

Yes

45. Min supply water temperature [°C]:

45

46. Max supply water temperature [°C]:

60

47. Display type:

LCD ProSmart soft touch

48. USB port:

Yes, for Firmware actualisation

49. Self-diagnostics:

Yes

50. Double rinse:

Yes

51. Wash pump type:

DuoFlow

52. Detergent dispenser:

Yes

53. Rinse aid dispenser:

Yes

54. Water consumption of the washing cycle [l/basket]:

0,8 - 1,4

55. Washing cycle time [s/basket]:

18 - 37

56. Rinse water temperature [°C]:

82

Technical data sheet

Technical parameters



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers

57. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

58. Program ProSpeed:

No

59. Program ProFessional:

No

60. Program ProFessional 2:

No

61. Program ProFessional 4:

No

62. Program ProFessional 6:

No

63. Program ProFessional 8:

No

64. Program ProFessional 10:

No

65. Program ProTemp:

No

66. Program ProSelf:

No

67. Program ProClean:

No

68. Program ProDrain:

No

69. Program ProEco:

No

70. Program ProNew:

No

71. Program ProLong:

No

72. Program ProGlass:

No

73. Program ProPlates:

No

74. Program ProCold:

No

75. Program ProWater:

No

76. Program ProActive:

No

77. Program ProActive 5:

No

78. Program ProActive 7:

No

79. Program ProSteel:

No

80. Program ProSan:

No

81. Program High Capacity:

Yes

82. Program General purpose:

Yes

83. Program Prolonged contact (DIN 10534):

Yes

84. Program Glasses:

Yes

Technical data sheet

Technical parameters



Rack conveyor dishwasher 200 racks/hour hot water, left exit

Model	SAP Code	00010033
A 200 ABT LX M Y	A group of articles - web	Tunel dishwashers

85. Cross-section of conductors CU [mm²]:

10

87. Diameter nominal:

DN 50

86. Water supply connection:

3/4"