

Product features

STEAMBOX gas convection oven 20x GN 1/1 Automatic cleaning Direct steam		
Model	SAP Code	00008602
STBD 2011 G	A group of articles - web	Convection machines
		– Steam type: Injection

- Steam type: Injection
 Number of GN / EN: 20
 GN / EN size in device: GN 1/1
 GN device depth: 65
- Control type: Touchscreen + buttons
- Display size: 9"
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Supersteam two steam saturation modes
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00008602	Type of gas	Natural Gas
Net Width [mm]	995	Steam type	Injection
Net Depth [mm]	835	Number of GN / EN	20
Net Height [mm]	1850	GN / EN size in device	GN 1/1
Net Weight [kg]	300.00	GN device depth	65
Power electric [kW]	0.800	Control type	Touchscreen + buttons
Loading	230 V / 1N - 50 Hz	Display size	9"
Power gas [kW]	36.000		





STEAMBOX gas convection oven 20x GN 1/1 Automatic cleaning Direct steam		
Model	SAP Code	00008602
STBD 2011 G	A group of articles - web	Convection machines

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

Touch screen display simple intuitive control with unique pictograms,

all in Czech the possibility of using preset programs or manual control

I

Weather systempatented device for measuring steam saturation in real

time and in steam mode, the only one on the market

4 Steam tuner
a control element that enables setting the exact
saturation of steam in the cooking chamber during the
cooking process

Pass-through door

the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen

Adaptation for roasting chickens

the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

Premix burner

the only burner with a turbo pre -mixing gas with air on the market

the structure of the burner to V which prevents backfill and banging

This design saves 30 % of gas compared to conventional burners

Automatic washing

integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler

Self -supporting shower

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

Six-speed fan, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

External temperature probe

temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe

Longitudinal insertion to GN

penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts

downloading service reports software upgrade recipe playback



Technical parameters

STEAMBOX gas convection ove	n 20x GN 1/1 Automatic	cleaning Direct steam
Model	SAP Code	00008602
STBD 2011 G	A group of articles - web	Convection machines
1. SAP Code: 00008602		14. Type of gas: Natural Gas
2. Net Width [mm]: 995		15. Material: AISI 304
3. Net Depth [mm]: 835		16. Exterior color of the device: Stainless steel
4. Net Height [mm]: 1850		17. Adjustable feet: Yes
5. Net Weight [kg]: 300.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
6. Gross Width [mm]: 1150		19. Stacking availability:
7. Gross depth [mm]: 1050		20. Control type: Touchscreen + buttons
8. Gross Height [mm]: 2100		21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
9. Gross Weight [kg]: 310.00		22. Steam type: Injection
10. Device type: Gas unit		23. Chimney for moisture extraction: Yes
11. Power electric [kW]: 0.800		24. Delayed start: Yes
12. Loading: 230 V / 1N - 50 Hz		25. Display size: 9"
13. Power gas [kW]:		26. Delta T heat preparation:

Yes

36.000



Technical parameters

STEAMBOX gas convection oven 2	0x GN 1/1 Automatic cl	eaning Direct steam
Model	SAP Code	00008602
STBD 2011 G	A group of articles - web	Convection machines
27. Automatic preheating: Yes		40. Sustaince box: Yes
28. Automatic cooling: Yes		41. Probe: Yes
29. Unified finishing of meals Easys	Service:	42. Shower: Hand winder
30. Night cooking: Yes		43. Distance between the layers [mm]: 70
31. Washing system: Closed - efficient use of water and repeated pumping	washing chemicals by	44. Smoke-dry function: Yes
32. Detergent type: Liquid washing detergent + liquid washing tablets	inse aid/vinegar or	45. Interior lighting: Yes
33. Multi level cooking: Drawer program - control of heat t dish separately	reatment for each	46. Low temperature heat treatment: Yes
34. Advanced moisture adjustment Supersteam - two steam saturation		47. Number of fans: 2
35. Slow cooking: from 50 °C		48. Number of fan speeds:
36. Fan stop: Immediate when the door is open	ed	49. Number of programs: 1000
37. Lighting type: LED lighting in the doors, on both	sides	50. USB port: Yes, for uploading recipes and updating firmware
38. Cavity material and shape: AISI 304, with rounded corners for	easy cleaning	51. Door constitution: Vented safety double glass, removable for easy cleaning

Yes

39. Reversible fan:

52. Number of preset programs:



Technical parameters

STEAMBOX gas convection oven 20	x GN 1/1 Automatic	GN 1/1 Automatic cleaning Direct steam	
Model	SAP Code	00008602	
STBD 2011 G	A group of articles - web	Convection machines	
53. Number of recipe steps: 9		59. GN / EN size in device: GN 1/1	
54. Minimum device temperature [°C	:	60. GN device depth: 65	
55. Maximum device temperature [° 300	C]:	61. Food regeneration: Yes	
56. Device heating type: Combination of steam and hot air		62. Connection to a ball valve: 1/2	
57. HACCP: Yes		63. Diameter nominal: DN 50	
58. Number of GN / EN:		64. Water supply connection:	

3/4"

20