

#### Product features

| STEAMBOX gas convection oven 10x GN 1/1 touch digital Automatic cleaning boiler |                           |  |
|---|---------------------------|--|
| Model   | SAP Code                  | 00011589   |
| SDBB 1011 GAM   | A group of articles - web | Convection machines  |
|   |                           | <ul> <li>Steam type: Symbiotic - boiler and injection combination (patent)</li> <li>Number of GN / EN: 10</li> <li>GN / EN size in device: GN 1/1</li> <li>GN device depth: 65</li> <li>Control type: Digital</li> <li>Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)</li> <li>Advanced moisture adjustment: Supersteam - two steam saturation modes</li> <li>Delta T heat preparation: Yes</li> <li>Automatic preheating: Yes</li> <li>Multi level cooking: No</li> <li>Door constitution: Vented safety double glass, removable for</li> </ul> |

| SAP Code            | 00011589           | Power gas [kW]         | 19.000  |
|---------------------|--------------------|------------------------|---|
| Net Width [mm]      | 860                | Type of gas            | Natural Gas   |
| Net Depth [mm]      | 795                | Steam type             | Symbiotic - boiler and injection combination (patent) |
| Net Height [mm]     | 1115               | Number of GN / EN      | 10  |
| Net Weight [kg]     | 178.00             | GN / EN size in device | GN 1/1  |
| Power electric [kW] | 1.700              | GN device depth        | 65  |
| Loading             | 230 V / 1N - 50 Hz | Control type           | Digital   |

easy cleaning





| odel          |   | SAP Code  | 000115              | 89  |
|---------------|---|---|---------------------|---|
| SDBB 1011 GAM |   | A group of articles - web                       | Convection machines |   |
| 1 2           | A symbiotic steam general simultaneous use of direct in maintenance of 100% humi  Digital display simple multi-line backlit dis | njection and boiler,<br>dity, or its regulation | 8                   | Premix burner  the only burner with a turbo pre -mixing gas with air on the market the structure of the burner to V which prevents backfill and banging This design saves 30 % of gas compared to conventional burners                      |
| 3             | weather system patented device for measuritime and in steam mode, th  |   | 9                   | Automatic washing integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler  |
| 4             | Steam tuner a control element that enab saturation of steam in the co   |   | 10                  | Self -supporting shower drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed  |
| 5             | Pass-through door the door is also built into the while full control is retained enables the distribution of t and the kitchen  | from the side of the cook                       | 11                  | Six-speed fan, reversible with automatic calculation of direction change in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually |
| 6             | Adaptation for roasting the chamber of the convect baked fat, the machine is ec collecting fat                                  | ion oven is designed to collect                 | 12                  | <b>External temperature probe</b> temperature probe located outside the cooking area choice of single or multipoint probe or vacuum probe   |
| 7             | A kit of two machines of connection kit allowing two top of each other  | •   | 13                  | <b>Longitudinal insertion to GN</b> penetration placed on the "depth" of the machine exchangeable for 600x400 sheet metal inserts   |



### Technical parameters

| STEAMBOX gas convection ov             | en 10x GN 1/1 touch digi  | tal Automatic cleaning boiler   |
|--|---------------------------|---|
| Model                                  | SAP Code                  | 00011589  |
| SDBB 1011 GAM                          | A group of articles - web | Convection machines   |
| <b>1. SAP Code:</b> 00011589           |                           | 14. Type of gas: Natural Gas  |
| 2. Net Width [mm]:<br>860              |                           | <b>15. Material:</b> AISI 304   |
| <b>3. Net Depth [mm]:</b> 795          |                           | <b>16. Exterior color of the device:</b> Stainless steel  |
| <b>4. Net Height [mm]:</b> 1115        |                           | <b>17. Adjustable feet:</b> Yes   |
| <b>5. Net Weight [kg]:</b> 178.00      |                           | <b>18. Humidity control:</b> MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)             |
| <b>6. Gross Width [mm]:</b> 955        |                           | 19. Stacking availability: Yes  |
| <b>7. Gross depth [mm]:</b> 920        |                           | 20. Control type: Digital   |
| 8. Gross Height [mm]: 1240             |                           | <b>21. Additional information:</b> possibility of reverse door opening - handle on the right side (must be specified when ordering) |
| 9. Gross Weight [kg]:<br>188.00        |                           | <b>22. Steam type:</b> Symbiotic - boiler and injection combination (patent)  |
| 10. Device type:<br>Combined unit      |                           | 23. Chimney for moisture extraction: Yes  |
| <b>11. Power electric [kW]:</b> 1.700  |                           | <b>24. Delta T heat preparation:</b> Yes  |
| <b>12. Loading:</b> 230 V / 1N - 50 Hz |                           | <b>25. Automatic preheating:</b> Yes  |
| 13. Power gas [kW]:                    |                           | 26. Automatic cooling:  |

Yes

19.000



### Technical parameters

| STEAMBOX gas convection oven   | 10x GN 1/1 touch digital  | l Automatic cleaning boiler   |  |
|--|---------------------------|---|--|
| Model  | SAP Code                  | 00011589  |  |
| SDBB 1011 GAM  | A group of articles - web | Convection machines   |  |
| <b>27. Unified finishing of meals Easy</b> No  | /Service:                 | <b>40. Shower:</b> volitelná  |  |
| 28. Night cooking:   |                           | <b>41. Distance between the layers [mm]:</b> 70                                       |  |
| 29. Washing system:  Closed - efficient use of water and washing chemicals by repeated pumping |                           | <b>42. Smoke-dry function:</b> No   |  |
| 30. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets     |                           | <b>43. Interior lighting:</b> Yes   |  |
| 31. Multi level cooking:   |                           | <b>44. Low temperature heat treatment:</b> Yes  |  |
| <b>32. Advanced moisture adjustment:</b> Supersteam - two steam saturation modes               |                           | <b>45. Number of fans:</b>  |  |
| <b>33. Slow cooking:</b> from 30 °C - the possibility of rising                                |                           | <b>46. Number of fan speeds:</b>  |  |
| <b>34. Fan stop:</b> Immediate when the door is opened   |                           | <b>47. Number of programs:</b> 99   |  |
| <b>35. Lighting type:</b> LED lighting in the doors, on both sides                             |                           | <b>48. USB port:</b> Yes, for uploading recipes and updating firmware                 |  |
| <b>36. Cavity material and shape:</b> AISI 304, with rounded corners for easy cleaning         |                           | <b>49. Door constitution:</b> Vented safety double glass, removable for easy cleaning |  |
| 37. Reversible fan: Yes  |                           | <b>50. Number of preset programs:</b> 40  |  |
| 38. Sustaince box: Yes   |                           | <b>51. Number of recipe steps:</b> 9  |  |
| 39. Probe: Optional  |                           | <b>52.</b> Minimum device temperature [°C]:   |  |



### Technical parameters

| STEAMBOX gas convection oven 10x GN 1/1 touch digital Automatic cleaning boiler |                           |  |  |
|---|---------------------------|--|--|
| Model SAP Code  |                           | 00011589   |  |
| SDBB 1011 GAM   | A group of articles - web | Convection machines                                  |  |
| 53. Maximum device temperature [°C]: 300  |                           | <b>59. Food regeneration:</b> Yes                    |  |
| <b>54. Device heating type:</b> Combination of steam and hot air                |                           | <b>60. Connection to a ball valve:</b> 1/2           |  |
| <b>55. HACCP:</b> Yes   |                           | <b>61.</b> Cross-section of conductors CU [mm²]: 0,5 |  |
| <b>56. Number of GN / EN:</b>   |                           | <b>62. Diameter nominal:</b> DN 50                   |  |
| 57. GN / EN size in device:  GN 1/1   |                           | 63. Water supply connection: 3/4"                    |  |

65

58. GN device depth:

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com