

Technical data sheet

Product features



Combi convection steam oven STEAMBOX electric 10x GN 1/1 . boiler levé otevírání dveří 400 V

Model	SAP Code	00012631
STBB 1011 EL	A group of articles - web	Convection machines



- Steam type: Symbiotic - boiler and injection combination (patent)
- Number of GN / EN: 10
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Touchscreen + buttons
- Display size: 9"
- Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Steamtuner - 5-stage system of setting steam saturation by controlled combination of production by boiler or injection
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: Drawer program - control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00012631	Steam type	Symbiotic - boiler and injection combination (patent)
Net Width [mm]	860	Number of GN / EN	10
Net Depth [mm]	795	GN / EN size in device	GN 1/1
Net Height [mm]	1115	GN device depth	65
Net Weight [kg]	168.00	Control type	Touchscreen + buttons
Power electric [kW]	16.500	Display size	9"
Loading	400 V / 3N - 50 Hz		

Technical data sheet

Technical drawing



Combi convection steam oven STEAMBOX electric 10x GN 1/1 . boiler levé otevírání dveří 400 V

Model	SAP Code	00012631
STBB 1011 EL	A group of articles - web	Convection machines



Technical data sheet

Product benefits



Combi convection steam oven STEAMBOX electric 10x GN 1/1 . boiler levé otevírání dveří 400 V

Model	SAP Code	00012631
STBB 1011 EL	A group of articles - web	Convection machines

1

A symbiotic steam generation system

simultaneous use of direct injection and boiler, maintenance of 100% humidity, possibly its regulation the only Slim type combi oven on the market with a boiler

- preparation of different dishes and cooking styles in an environment precisely set for the food or dish

2

Touch screen display

simple intuitive control with unique pictograms, all in Czech the possibility of using preset programs or manual control

- help with cooking even for less skilled cooks, safe baking even in the absence of an operator; create your own recipes; easy to use

3

Weather system

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

- precise information for the operator about the steam saturation in the cooking area

4

Steam tuner

a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process

- possibility of cooking different types of cuisine, from very moist steam for typical Czech dishes to low-saturated steam for e.g. French cuisine

5

Pass-through door

the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen

- the chef can dispense the food through the convecto machine, the customer can see the preparation and maintenance of the food during dispensing

6

Adaptation for roasting chickens

the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat

- grease does not drain into the sewer, does not destroy the machine's waste system

7

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation of the lower combi oven

- allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

8

Premix burner

the only burner with a turbo pre-mixing gas with air on the market

the structure of the burner to V which prevents backfill and banging

This design saves 30 % of gas compared to conventional burners

- faster heat-up faster more comfortable operation

9

Automatic washing

integrated chamber washing system possibility to use liquid and tablet detergents

option to use vinegar as a rinse agent

the system simultaneously descales the micro-boiler

- the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 1% hygienic quality

10

Self-supporting shower

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

- allows food in the food processor to be rinsed out - if necessary to speed up cooling

11

Six-speed fan, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

- allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

Technical data sheet

Technical parameters



Combi convection steam oven STEAMBOX electric 10x GN 1/1 . boiler levé otevírání dveří 400 V

Model	SAP Code	00012631
STBB 1011 EL	A group of articles - web	Convection machines

1. SAP Code:

00012631

2. Net Width [mm]:

860

3. Net Depth [mm]:

795

4. Net Height [mm]:

1115

5. Net Weight [kg]:

168.00

6. Gross Width [mm]:

1000

7. Gross depth [mm]:

1000

8. Gross Height [mm]:

1300

9. Gross Weight [kg]:

180.00

10. Device type:

Electric unit

11. Power electric [kW]:

16.500

12. Loading:

400 V / 3N - 50 Hz

13. Material:

AISI 304

14. Exterior color of the device:

Stainless steel

15. Adjustable feet:

Yes

16. Humidity control:

MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)

17. Stacking availability:

Yes

18. Control type:

Touchscreen + buttons

19. Additional information:

possibility of reverse door opening - handle on the right side (must be specified when ordering)

20. Steam type:

Symbiotic - boiler and injection combination (patent)

21. Chimney for moisture extraction:

Yes

22. Delayed start:

Yes

23. Display size:

9"

24. Delta T heat preparation:

Yes

25. Automatic preheating:

Yes

26. Automatic cooling:

Yes

Technical data sheet

Technical parameters



Combi convection steam oven STEAMBOX electric 10x GN 1/1 . boiler levé otevírání dveří 400 V

Model	SAP Code	00012631
STBB 1011 EL	A group of articles - web	Convection machines

27. Unified finishing of meals EasyService:

Yes

28. Night cooking:

Yes

29. Washing system:

Closed - efficient use of water and washing chemicals by repeated pumping

30. Detergent type:

Liquid washing detergent + liquid rinse aid/vinegar or washing tablets

31. Multi level cooking:

Drawer program - control of heat treatment for each dish separately

32. Advanced moisture adjustment:

Steamtuner - 5-stage system of setting steam saturation by controlled combination of production by boiler or injection

33. Slow cooking:

from 30 °C - the possibility of rising

34. Fan stop:

Immediate when the door is opened

35. Lighting type:

LED lighting in the doors, on both sides

36. Cavity material and shape:

AISI 304, with rounded corners for easy cleaning

37. Reversible fan:

Yes

38. Sustance box:

Yes

39. Heating element material:

Incoloy

40. Probe:

Yes

41. Shower:

Hand winder

42. Distance between the layers [mm]:

70

43. Smoke-dry function:

Yes

44. Interior lighting:

Yes

45. Low temperature heat treatment:

Yes

46. Number of fans:

1

47. Number of fan speeds:

6

48. Number of programs:

1000

49. USB port:

Yes, for uploading recipes and updating firmware

50. Door constitution:

Vented safety double glass, removable for easy cleaning

51. Number of preset programs:

100

52. Number of recipe steps:

9

Technical data sheet

Technical parameters



Combi convection steam oven STEAMBOX electric 10x GN 1/1 . boiler levé otevírání dveří 400 V

Model	SAP Code	00012631
STBB 1011 EL	A group of articles - web	Convection machines

53. Minimum device temperature [°C]:

30

54. Maximum device temperature [°C]:

300

55. Device heating type:

Combination of steam and hot air

56. HACCP:

Yes

57. Number of GN / EN:

10

58. GN / EN size in device:

GN 1/1

59. GN device depth:

65

60. Food regeneration:

Yes

61. Cross-section of conductors CU [mm²]:

5

62. Diameter nominal:

DN 50

63. Water supply connection:

3/4"