

Technical data sheet

Product features



Cooking range induction 4 zones

Model	SAP Code	00013593
PCID-88ET	A group of articles - web	Stoves



- Device type: Electric unit
- Power consumption of the zone 1 [kW]: 5
- Power consumption of the zone 2 [kW]: 5
- Power consumption of the zone 3 [kW]: 5
- Power consumption of the zone 4 [kW]: 5
- Protection of controls: IPX5
- Material: Stainless steel

SAP Code	00013593	Number of zones	4
Net Width [mm]	800	Power consumption of the zone 1 [kW]	5
Net Depth [mm]	800	Power consumption of the zone 2 [kW]	5
Net Height [mm]	422	Power consumption of the zone 3 [kW]	5
Net Weight [kg]	43.00	Power consumption of the zone 4 [kW]	5
Power electric [kW]	20.000	Ceramic glass dimensions [mm x mm]	750 x 770
Loading	400 V / 3N - 50 Hz		

Technical drawing



The technical drawing illustrates the PCID-84ET fireproof safe through multiple views:

- Top View:** Shows two door configurations. The left configuration has dimensions A=400 mm, 180 mm, 170 mm, and 90 mm. The right configuration has dimension A=800 mm.
- Isometric View:** Displays the safe's exterior with two circular ventilation grilles on the top panel and a handle on the right side.
- Front View (Left):** Shows the safe's profile with overall width 800 mm, height 295.8 mm, and internal depth 215 mm. It includes mounting bracket details with dimensions 85.2 mm, 36.7 mm, and 200 mm.
- Front View (Right):** Shows the safe's profile with overall width A mm, height 24.2 mm, and internal depth 10 mm. It includes mounting bracket details with dimensions 200 mm and 120 mm.
- Side View:** Shows the safe's side profile with dimensions 35 mm and 49 mm.
- Bottom View:** Shows the base of the safe with dimensions 400 - 600 - 800 mm and 400 - 600 - 800 mm.
- Detail Views:** Includes detailed views of the locking mechanism (B) and the base plate (C).

Tabella			
Descrizione	A	C	D
PCID-84ET	400 mm	100 cm ²	150 cm ²

tel.: +420 381 582 284
e-mail: rmgastro@rmgastro.com
web: www.rmgastro.com

Technical data sheet

Technical parameters



Cooking range induction 4 zones

Model	SAP Code	00013593
PCID-88ET	A group of articles - web	Stoves

1. SAP Code:

00013593

2. Net Width [mm]:

800

3. Net Depth [mm]:

800

4. Net Height [mm]:

422

5. Net Weight [kg]:

43.00

6. Gross Width [mm]:

830

7. Gross depth [mm]:

970

8. Gross Height [mm]:

540

9. Gross Weight [kg]:

50.00

10. Device type:

Electric unit

11. Construction type of device:

Drop-in

12. Power electric [kW]:

20.000

13. Loading:

400 V / 3N - 50 Hz

14. Protection of controls:

IPX5

15. Material:

Stainless steel

16. Worktop type:

Molded - comfortable cleaning maintenance

17. Worktop material:

AISI 304

18. Worktop Thickness [mm]:

2.00

19. Number of zones:

4

20. Power consumption of the zone 1 [kW]:

5

21. Power consumption of the zone 2 [kW]:

5

22. Power consumption of the zone 3 [kW]:

5

23. Power consumption of the zone 4 [kW]:

5

24. Power control type:

knob control

25. Number of power control stages:

6

26. Service accessibility:

From the front by removing the front panel and waste fluid containers

27. Number of burners/hot plates:

4

28. Type of electric cooking zones:

Induction

Technical data sheet

Technical parameters



Cooking range induction 4 zones

Model	SAP Code	00013593
PCID-88ET	A group of articles - web	Stoves

29. Ceramic glass dimensions [mm x mm]:

750 x 770

30. Cross-section of conductors CU [mm²]:

10