

# Technical data sheet

## Product features



### Fry-top griddle plate 100x45 electric grooved without cabinet 400 V

|              |                                  |                         |
|--------------|----------------------------------|-------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00001121                |
| FTRT-610ET   | <b>A group of articles - web</b> | Grills and grill plates |



- Top type: Grooved
- Griddle dimensions [mm x mm]: 995 x 450
- Griddle thickness [mm]: 14.00
- Worktop material: Stainless steel
- Maximum device temperature [°C]: 300

|                        |          |                                     |                    |
|------------------------|----------|-------------------------------------|--------------------|
| <b>SAP Code</b>        | 00001121 | <b>Power electric [kW]</b>          | 11.250             |
| <b>Net Width [mm]</b>  | 1000     | <b>Loading</b>                      | 400 V / 3N - 50 Hz |
| <b>Net Depth [mm]</b>  | 600      | <b>Griddle dimensions [mm x mm]</b> | 995 x 450          |
| <b>Net Height [mm]</b> | 280      | <b>Top type</b>                     | Grooved            |
| <b>Net Weight [kg]</b> | 80.00    |                                     |                    |

# Technical drawing



RM GASTRO, s.r.o.,  
Třída Čs. armády 816,  
391 81 Veselí nad Lužnicí 1, ID:49825062

# Technical data sheet

## Product benefits



### Fry-top griddle plate 100x45 electric grooved without cabinet 400 V

|              |                                  |                         |
|--------------|----------------------------------|-------------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00001121                |
| FTRT-610ET   | <b>A group of articles - web</b> | Grills and grill plates |

1

#### All-stainless design

long life  
resistance of AISI 304 stainless steel material  
the material does not cut

- savings on service interventions
- easier and faster operation

2

#### Degree of protection of the control elements IPX5

maintenance-free system  
resistance to splash water  
long life

- savings on service interventions
- easy cleaning and maintenance of equipment

3

#### Outlet for waste liquids

ensures that oil drips into the socket

- easy maintenance
- easy cleaning

4

#### High detachable hem

better hygienic conditions  
preventing grease from splashing onto ancillary equipment

- easy maintenance
- easy cleaning

5

#### Ribbed steel plate

fast heat transfer and the surface will not be scratched  
a good warming of the meat with a groove

- time-saving in food preparation
- easy preparation of good-looking food

6

#### Cooking unit for use on a table or on a base

variable use  
the possibility of placement in smaller spaces

- easy handling
- cost savings on substructure

# Technical data sheet

## Technical parameters



### Fry-top griddle plate 100x45 electric grooved without cabinet 400 V

|                   |                                  |                         |
|-------------------|----------------------------------|-------------------------|
| <b>Model</b>      | <b>SAP Code</b>                  | 00001121                |
| <b>FTRT-610ET</b> | <b>A group of articles - web</b> | Grills and grill plates |

**1. SAP Code:**

00001121

**2. Net Width [mm]:**

1000

**3. Net Depth [mm]:**

600

**4. Net Height [mm]:**

280

**5. Net Weight [kg]:**

80.00

**6. Gross Width [mm]:**

1030

**7. Gross depth [mm]:**

690

**8. Gross Height [mm]:**

610

**9. Gross Weight [kg]:**

88.00

**10. Device type:**

Electric unit

**11. Construction type of device:**

Table top

**12. Power electric [kW]:**

11.250

**13. Loading:**

400 V / 3N - 50 Hz

**14. Protection of controls:**

IPX5

**15. Exterior color of the device:**

Stainless steel

**16. Material:**

AISI 304 top plate and cladding

**17. Indicators:**

operation and warm-up

**18. Worktop material:**

Stainless steel

**19. Worktop Thickness [mm]:**

2.50

**20. Maximum device temperature [°C]:**

300

**21. Minimum device temperature [°C]:**

50

**22. Service accessibility:**

Trough the frontal panel

**23. Safety thermostat:**

Yes

**24. Adjustable feet:**

Yes

**25. Griddle dimensions [mm x mm]:**

995 x 450

**26. Griddle thickness [mm]:**

14.00

**27. Top type:**

Grooved

**28. Cross-section of conductors CU [mm²]:**

4