

Product features

| STEAMBOX gas convection oven 20x GN 2/1 Automatic cleaning Direct steam | | | |
|---|---------------------------|-------------------------|--|
| Model | SAP Code | 00008603 | |
| STBD 2021 G | A group of articles - web | Convection machines | |
| | | - Steam type: Injection | |

Number of GN / EN: 20
GN / EN size in device: GN 2/1
GN device depth: 65

- Control type: Touchscreen + buttons

- Display size: 9"

 Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)

Advanced moisture adjustment: Supersteam - two steam saturation modes

- Delta T heat preparation: Yes

- Automatic preheating: Yes

 Multi level cooking: Drawer program - control of heat treatment for each dish separately

Door constitution: Vented safety double glass, removable for easy cleaning

| SAP Code | 00008603 | Type of gas | Natural Gas |
|---------------------|--------------------|------------------------|-----------------------|
| Net Width [mm] | 1200 | Steam type | Injection |
| Net Depth [mm] | 910 | Number of GN / EN | 20 |
| Net Height [mm] | 1850 | GN / EN size in device | GN 2/1 |
| Net Weight [kg] | 400.00 | GN device depth | 65 |
| Power electric [kW] | 1.600 | Control type | Touchscreen + buttons |
| Loading | 230 V / 1N - 50 Hz | Display size | 9" |
| Power gas [kW] | 56.000 | | |



Technical drawing

| STEAMBOX gas convection oven 20x GN 2/1 Automatic cleaning Direct steam | | | |
|---|---------------------------|---------------------|--|
| Model | SAP Code | 00008603 | |
| STBD 2021 G | A group of articles - web | Convection machines | |





| STEAMBOX gas convection oven 20x GN 2/1 Automatic cleaning Direct steam | | |
|---|------------|---------------------|
| Model | SAP Code | 00008603 |
| STBD 2021 G | A group of | Convection machines |

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

Touch screen display

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control

 help with cooking even for less skilled cooks, safe baking even in the absence of an operator; create your own recipes; easy to use

Weather system

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

- precise information for the operator about the steam saturation in the cooking area

Steam tuner

a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process

 possibility of cooking different types of cuisine, from very moist steam for typical Czech dishes to lowsaturated steam for e.g. French cuisine

Pass-through door

the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen

- the chef can dispense the food through the convecto machine, the customer can see the preparation and maintenance of the food during dispensing

Adaptation for roasting chickens

the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat

- grease does not drain into the sewer, does not destroy the machine's waste system

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

Premix burner

the only burner with a turbo pre-mixing gas with air on the market

the structure of the burner to V which prevents backfill and banging

This design saves 30 % of gas compared to conventional burners

faster heat-up faster more comfortable operation

Automatic washing

integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler

the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 1% hygienic quality

Self-supporting shower

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

- allows food in the food processor to be rinsed out - if necessary to speed up cooling

Six-speed fan, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed



Technical parameters

| STEAMBOX gas convection oven 2 | 20x GN 2/1 Automatic c | leaning Direct steam |
|--|---------------------------|---|
| Model | SAP Code | 00008603 |
| STBD 2021 G | A group of articles - web | Convection machines |
| 1. SAP Code: 00008603 | | 14. Type of gas: Natural Gas |
| 2. Net Width [mm]: 1200 | | 15. Material: AISI 304 |
| 3. Net Depth [mm]: 910 | | 16. Exterior color of the device: Stainless steel |
| 4. Net Height [mm]: 1850 | | 17. Adjustable feet: Yes |
| 5. Net Weight [kg]: 400.00 | | 18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented) |
| 6. Gross Width [mm]: 1320 | | 19. Stacking availability: No |
| 7. Gross depth [mm]: 1130 | | 20. Control type: Touchscreen + buttons |
| 8. Gross Height [mm]: 2100 | | 21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering) |
| 9. Gross Weight [kg]: 410.00 | | 22. Steam type: Injection |
| 10. Device type: Gas unit | | 23. Chimney for moisture extraction: Yes |
| 11. Power electric [kW]: 1.600 | | 24. Delayed start: Yes |
| 12. Loading: 230 V / 1N - 50 Hz | | 25. Display size: 9" |
| 13. Power gas [kW]: 56.000 | | 26. Delta T heat preparation: Yes |



Technical parameters

| STEAMBOX gas convection over | n 20x GN 2/1 Automatic cl | eaning Direct steam |
|---|---------------------------|---|
| Model | SAP Code | 00008603 |
| STBD 2021 G | A group of articles - web | Convection machines |
| 27. Automatic preheating: Yes | | 40. Sustaince box: Yes |
| 28. Automatic cooling: Yes | | 41. Probe: Yes |
| 29. Unified finishing of meals EasyService: Yes | | 42. Shower: Hand winder |
| 30. Night cooking: Yes | | 43. Distance between the layers [mm]: 70 |
| 31. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping | | 44. Smoke-dry function: Yes |
| 32. Detergent type: Liquid washing detergent + liqui washing tablets | d rinse aid/vinegar or | 45. Interior lighting: Yes |
| 33. Multi level cooking: Drawer program - control of head dish separately | t treatment for each | 46. Low temperature heat treatment: Yes |
| 34. Advanced moisture adjustment: Supersteam - two steam saturation modes | | 47. Number of fans: 2 |
| 35. Slow cooking: from 50 °C | | 48. Number of fan speeds: |
| 36. Fan stop: Immediate when the door is ope | ened | 49. Number of programs: 1000 |
| 37. Lighting type: LED lighting in the doors, on bot | h sides | 50. USB port: Yes, for uploading recipes and updating firmware |
| 38. Cavity material and shape: AISI 304, with rounded corners for | or easy cleaning | 51. Door constitution: Vented safety double glass, removable for easy cleaning |
| | | |

Yes

39. Reversible fan:

52. Number of preset programs:



Technical parameters

| STEAMBOX gas convection oven 20x GN 2/1 Automatic cleaning Direct steam | | | |
|---|---------------------------|--|--|
| Model | SAP Code | 00008603 | |
| STBD 2021 G | A group of articles - web | Convection machines | |
| 53. Number of recipe steps: 9 | | 59. GN / EN size in device: GN 2/1 | |
| 54. Minimum device temperature [°C]: 50 | | 60. GN device depth: 65 | |
| 55. Maximum device temperature [°C]: 300 | | 61. Food regeneration: Yes | |
| 56. Device heating type: Combination of steam and hot air | | 62. Connection to a ball valve: 1/2 | |
| 57. HACCP: Yes | | 63. Diameter nominal: DN 50 | |
| 58. Number of GN / EN: | | 64. Water supply connection: | |

3/4"

20