Technical data sheet

Product features

Undercounter dishwasher double skin softener 50x50 400 V / 3N		
Model	**SAP Code**	00011292
TTA 52 TS ABT	**A group of articles - web**	Undercounter, continuous and black ware dishwasher



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD multifunction display
- Number of programs: 13
- Number of skin: 2
- Door clear height [mm]: 285
- Rack size [mm]: 500 x 500
- Drain pump: Yes
- Water consumption of the washing cycle [l/basket]: 2,2
- Washing cycle time [s/basket]: 90-120-150
- Detergent and rinse pump system: Accurate dosing with a peristaltic pump
- Wash pump type: DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: Double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste


SAP Code	00011292	**Boiler power [kW]**	4.900
Net Width [mm]	600	**Basin volume [l]**	15
Net Depth [mm]	600	**Tank power [kW]**	1.400
Net Height [mm]	720	**Water consumption of the wash-ing cycle [l/basket]**	2,2
Net Weight [kg]	56.00	**Washing cycle time [s/basket]**	90-120-150
Power electric [kW]	6.770	**Door clear height [mm]**	285
Loading	400 V / 3N - 50 Hz	**Rack size [mm]**	500 x 500
Boiler capacity [l]	6.00		


RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical drawing

Undercounter dishwasher double skin softener 50x50 400 V / 3N		
Model	**SAP Code**	00011292
TTA 52 TS ABT	**A group of articles - web**	Undercounter, continuous and black ware dishwasher





RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Product benefits

Undercounter dishwasher double skin softener 50x50 400 V / 3N		
Model	**SAP Code**	00011292
TTA 52 TS ABT	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

1 Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2 Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning
- increased user comfort

3 LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4 Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5 Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6 Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7 Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8 Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

9 Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

10 Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

11 Fast heating

performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Undercounter dishwasher double skin softener 50x50 400 V / 3N		
Model	**SAP Code**	00011292
TTA 52 TS ABT	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

1. **SAP Code:**
   00011292
2. **Net Width [mm]:**
   600
3. **Net Depth [mm]:**
   600
4. **Net Height [mm]:**
   720
5. **Net Weight [kg]:**
   56.00
6. **Gross Width [mm]:**
   690
7. **Gross depth [mm]:**
   670
8. **Gross Height [mm]:**
   770
9. **Gross Weight [kg]:**
   64.00
10. **Device type:**
    Electric unit
11. **Control type:**
    Digital
12. **Material:**
    Stainless steel
13. **Power electric [kW]:**
    6.770
14. **Loading:**
    400 V / 3N - 50 Hz
15. **Additional information:**
    Also possible: 230 V / 3N or 230 V / 1N (must be specified when ordering)
16. **Rack size [mm]:**
    500 x 500
17. **Number of programs:**
    13
18. **Opening of device:**
    Tilting down
19. **Door clear height [mm]:**
    285
20. **Adjustable feet:**
    Yes
21. **Number of skin:**
    2
22. **Self-cleaning cycle:**
    Yes
23. **Boiler capacity [l]:**
    6.00
24. **Boiler power [kW]:**
    4.900
25. **Basin volume [l]:**
    15
26. **Tank power [kW]:**
    1.400
27. **Number of arms for both rinsing and washing:**
    2
28. **Arm connection:**
    Hand loosen/tighten screw

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Undercounter dishwasher double skin softener 50x50 400 V / 3N		
Model	**SAP Code**	00011292
TTA 52 TS ABT	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

29. Washing arm type:
Rotatable two-pronged

30. Washing arm material:
Stainless steel

31. Atmospheric boiler with rinse pump:
Yes

32. Rinsing arm type:
Rotating two-pronged

33. Rinsing arm material:
Stainless steel

34. Deep drawn tank:
Yes

35. Rack support:
Pressed

36. Tank surface strainers:
stainless steel

37. Drain filter:
Double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

38. Thermostop:
Yes

39. Boiler thermostat adjust:
Yes

40. Rack feed capacity:
40-30-24

41. Detergent and rinse pump system:
Accurate dosing with a peristaltic pump

42. Energy Saving system:
Energy saving system due to lowering the boiler temperature

43. Rinse system:
Composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure

44. Heating system:
System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

45. Quick heating system:
System for rapid heating of water in the tank

46. Hot water electric valve:
Yes

47. Closing door system:
Reduces noise, dampens the door stop, which could cause damage to dishes

48. Display type:
LCD multifunction display

49. USB port:
Yes, for Firmware actualisation

50. Drain pump:
Yes

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Undercounter dishwasher double skin softener 50x50 400 V / 3N		
Model	**SAP Code**	00011292
TTA 52 TS ABT	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

51. Self-diagnostics:
Yes

52. Wash pump type:
DuoFlow

53. Detergent dispenser:
Yes

54. Rinse aid dispenser:
Yes

55. Water consumption of the washing cycle [l/basket]:
2,2

56. Washing cycle time [s/basket]:
90-120-150

57. Rinse water temperature [°C]:
80

58. Standard equipment for device:
1x glass basket, 1x plate basket, 1x cutlery basket

59. Program ProSpeed:
Yes

60. Program ProFessional:
Yes

61. Program ProTemp:
Yes

62. Program ProClean:
Yes

63. Program ProDrain:
Yes

64. Program ProEco:
Yes

65. Program ProNew:
Yes

66. Program ProLong:
Yes

67. Program ProGlass:
Yes

68. Program ProWater:
Yes

69. Program ProActive:
Yes

70. Program ProSteel:
Yes

71. Program ProSan:
Yes

72. Cross-section of conductors CU [mm²]:
1,5

73. Water supply connection:
3/4”

74. Diameter nominal:
DN 50

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062