



Hood type dishwasher double skin heat recovery system 50x60 - 400 V		
Model	SAP Code	00011299
TT 162 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher




- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD multifunction display
- Number of programs: 13
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 600 x 500
- Water consumption of the washing cycle [l/basket]: 2,4
- Washing cycle time [s/basket]: 60-90-180
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: Evolution3 double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

SAP Code	00011299	Boiler power [kW]	7.000
Net Width [mm]	835	Basin volume [l]	30
Net Depth [mm]	788	Tank power [kW]	2.500
Net Height [mm]	2265	Water consumption of the washing cycle [l/basket]	2,4
Net Weight [kg]	120.00	Washing cycle time [s/basket]	60-90-180
Power electric [kW]	11.000	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	600 x 500
Boiler capacity [l]	12.00		



Technical drawing

Hood type dishwasher double skin heat recovery system 50x60 - 400 V		
Model	SAP Code	00011299
TT 162 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher







Hood type dishwasher double skin heat recovery system 50x60 - 400 V		
Model	SAP Code	00011299
TT 162 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

round construction with stainless steel, rounded edges, Deep-drawn bathtub

Stainless steel outer shell construction

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

3 LED Display proScreen 4 local display + 2 LED strips

Double pump
unique two-way DuoFlow pump

Molded basket supports
guide rails for the baskets molded from the body of the dishwasher

Detergent dispensers
two detergent and rinse aid dispensers

The chamber filter system
the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

Energy saving energy saving system due to lowering the temperature of the boiler

Protection of fragile dishes
softstart system for gradual start of washing programs to protect fragile dishes

Double shell construction

stainless steel construction with insulated double jacket

Fast heating
performance management allows the current running of the boiler and basins body

Possibility of recovery
saving up to 40% of boiler energy
improves the comfort environment of the workplace
environment without steam
saves water

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com



Technical parameters

Hood type dishwasher double s	kin heat recovery syst	em 50x60 - 400 V
Model	SAP Code	00011299
TT 162 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
1. SAP Code: 00011299		15. Number of programs: 13
2. Net Width [mm]: 835		16. Opening of device: Flip up
3. Net Depth [mm]: 788		17. Door clear height [mm]: 465
4. Net Height [mm]: 2265		18. Adjustable feet: Yes
5. Net Weight [kg]: 120.00		19. Number of skin:
6. Gross Width [mm]: 838		20. Self-cleaning cycle: Yes
7. Gross depth [mm]: 885		21. Boiler capacity [l]: 12.00
8. Gross Height [mm]: 2314		22. Boiler power [kW]: 7.000
9. Gross Weight [kg]: 130.00		23. Basin volume [l]:
10. Device type: Electric unit		24. Tank power [kW]: 2.500
11. Control type: Digital		25. Number of arms for both rinsing and washing:
12. Material: Stainless steel		26. Arm connection: Hand loosen/tighten screw
13. Power electric [kW]: 11.000		27. Washing arm type: Rotatable two-pronged
14. Loading:		28. Washing arm material:

400 V / 3N - 50 Hz

Stainless steel





Hood t	type dishwasher double skir	n heat recovery system 5	60x60 - 400 V
Model		SAP Code	00011299
TT 16	62 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
29. Atmospheric boiler with rinse pump: Yes		ımp:	39. Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
	30. Rinsing arm type: Rotating two-pronged		40. Energy Saving system: EnergySaving - Energy saving system due to lowering the boiler temperature
	31. Rinsing arm material: Stainless steel		41. Rinse system: ProRinse - composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure
32. Deep Yes	32. Deep drawn tank: Yes		42. Heating system: HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle
	33. Rack support: Pressed		43. Quick heating system: QuickReady - System for rapid heating of water in the tank
	34. Tank surface strainers: stainless steel		44. Lift system: ProGlide - Required lifting force equals 3 kg thanks to counterweights and gentle guidance, reduces operator fatigue
Evolu parti	35. Drain filter: Evolution3 - double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste		45. Heat recovery: 1 copper-aluminum battery - saving up to 40% of the energy needed to heat the water in the boiler, at the same time, by absorbing the released steam, it eliminates the need to use a hood
36. Ther Yes	rmostop:		46. Hot water electric valve: Yes

Yes

37. Boiler thermostat adjust:

38. Rack feed capacity:

60-40-20

47. Closing door system:

48. Rack size [mm]: 600 x 500

could cause damage to dishes

ProSoft - Reduces noise, dampens the door stop, which



Technical parameters

Hood type dishwasher double skin	heat recovery system	1 50x60 - 400 V
Model	SAP Code	00011299
TT 162 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
49. Display type: LCD multifunction display		63. Program ProTemp: Yes
50. Location of control panel: On the top		64. Program ProClean: Yes
51. USB port: Yes, for Firmware actualisation		65. Program ProDrain: Yes
52. Drain pump: Yes		66. Program ProEco: Yes
53. Self-diagnostics: Yes		67. Program ProNew: Yes
54. Wash pump type: two-way - DuoFlow		68. Program ProLong: Yes
55. Detergent dispenser: Yes		69. Program ProGlass: Yes
56. Rinse aid dispenser: Yes		70. Program ProWater: Yes
57. Water consumption of the washing cycle [l/basket]: 2,4		71. Program ProActive: Yes
58. Washing cycle time [s/basket]: 60-90-180		72. Program ProSteel: Yes
59. Rinse water temperature [°C]: 80		73. Program ProSan: Yes
60. Standard equipment for device: 1x glass basket, 1x plate basket, 1x cutlery basket		74. Cross-section of conductors CU [mm²]: 2,5
61. Program ProSpeed: Yes		75. Water supply connection: 3/4"
62. Program ProFessional:		76. Diameter nominal:

Yes

DN 50